

## Laser Blade XS



Design iGuzzini

iGuzzini

Last information update: May 2025

### Product configuration: 115B

115B: Linear module LB XS for 48V Superrail track - DALI Powerline - HC 10 cells



### Product code

115B: Linear module LB XS for 48V Superrail track - DALI Powerline - HC 10 cells

### Technical description

Fixed linear module with 10 optic elements complete with adapter for installation on a Superrail LV track. The adapter made of a thermoplastic material includes the DC/DC driver circuit with a DALI dimmable function. Integrated «Powerline» technology allows each light module on the track to be adjusted separately. Fixed optics with metallised thermoplastic high definition Opti-Beam reflectors. Despite the ultracompact size of the product, the patented technology of the optic system guarantees an efficient luminous flux and a high level of controlled glare visual comfort. Main body made of extruded aluminium. A rapid tool-free system for connecting the adapter electrically and mechanically to the track.

### Installation

Mechanical fastening with adapter on track.

### Colour

White (01) | Black / Black (43) | Black / White (47)

### Mounting

Low voltage track

### Wiring

Integrated DC/DC LED driver in adapter - direct connection on 48V track. Track power supply unit to be ordered separately.

Complies with EN60598-1 and pertinent regulations



### Technical data

Im system:	1618.5	Colour temperature [K]:	3500
W system:	21.9	MacAdam Step:	2
Im source:	1950	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25C)
W source:	20	Voltage [Vin]:	48
Luminous efficiency (Im/W, real value):	73.9	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0.0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	83	Number of optical assemblies:	1
Beam angle [°]:	43°	LED current [mA]:	0.7
CRI:	90	Control:	DALI