

Last information update: April 2025

**Product configuration: 2753**

2753: Spotlight with bracket - RGBW - Integrated control card - Remote power supply - Super Spot optic

**Product code**

2753: Spotlight with bracket - RGBW - Integrated control card - Remote power supply - Super Spot optic

**Technical description**

Spotlight designed to use RGBW (Red Green Blue White 3000K) LED lamps, a Super Spot optic and a DMX512-RDM control. Consists of a die-cast aluminium optical assembly, bracket and box for the power supply with a clear tempered sodium-calcium safety glass cover. The luminaire is fitted with a double cable gland for pass-through wiring. The optical assembly can be adjusted on a horizontal plane at an angle between -50° / +90°. Agorà is fitted with a graduated scale and mechanical locking device for positioning. The optical system is Opti Beam Lens. The electronic power supply is remote whereas the DMX driver is integrated in the product and compatible with remote management systems. Both indoor (diffuser glass covers, lamellar louvers and refractors for elliptical light) and outdoor accessories (cylindrical screens, visors and protective grilles) can be used. All external screws used are made of A2 stainless steel.

**Installation**

Floor, ceiling or wall-mounted installation.

**Colour**

White (01) | Black (04) | Grey (15) | Rust Brown (F5)

**Weight (Kg)**

14.16

**Wiring**

Double PG.

Complies with EN60598-1 and pertinent regulations




IK08

IP66


**Technical data**

Im system:	6096	Colour temperature [K]:	RGBW - 3000K
W system:	94.4	Life Time LED 1:	100,000h - L80 - B10 (Ta 25°C)
Im source:	8350	Life Time LED 2:	92,000h - L80 - B10 (Ta 40°C)
W source:	82	Lamp code:	LED
Luminous efficiency (Im/W, real value):	64.6	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	73	Intervalllo temperatura ambiente:	from -30°C to 50°C.
Beam angle [°]:	8°	LED current [mA]:	230
CRI (typical):	82	Control:	DMX-RDM

# Polar



# Isolux



# Illuminances

