

Last information update: February 2025

Product configuration: 439A

439A: SIPARIO Ø86 spotlight - DALI - Flood - OBReflector -

**Product code**

439A: SIPARIO Ø86 spotlight - DALI - Flood - OBReflector -

Technical description

Ø86 adjustable spotlight with adapter for installation on a base or electrified track. LED lamp with C.O.B. (Chip on board) technology, -CRI90- high colour rendering and 3500K tone.

Die-cast aluminium body with thermoplastic rear cap and front ring (Mass-Balance). The product can be rotated by 360° around the vertical axis with a mechanical lock and tilted by 90° relative to the horizontal plane. Passive heat dissipation.

OptiBeam Reflector optical system with Flood optic. Anti-scratch reflector made of P.V.D. (Physical Vapour Deposition) aluminium that can provide optimum performance in terms of light efficiency.

Dimmable electronic DALI-2 power supply integrated in the body of the luminaire.

Spotlight with Push&Go system designed to facilitate and safely accelerate the connection between product and optic accessory.

Mechanically disconnecting the accessory allows it to be disengaged but not dropped. Three internal accessories and one external one can be used simultaneously. All internal accessories rotate 360° about the spotlight longitudinal axis.

Installation

Base or mains voltage track.

Colour

White (01) | Matte black (V0)

Weight (Kg)

0.77

Mounting


three circuit track

Complies with EN60598-1 and pertinent regulations


**Technical data**

Im system:	2279	CRI (minimum):	90
W system:	21.1	Colour temperature [K]:	3500
Im source:	2590	MacAdam Step:	2
W source:	19	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (Im/W, 108 real value):		Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	88	Number of optical assemblies:	1
Beam angle [°]:	35°	Control:	DALI-2

Polar

Imax=6045 cd		Lux			
90°	180°	h	d	Em	Emax
		2	1.2	1199	1511
		4	2.5	300	378
		6	3.7	133	168
		8	5	75	94
α=35°					

Isolux



UGR diagram

Corrected UGR values (at 2590 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceiling		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim		viewed crosswise					viewed endwise				
x	y										
2H	2H	8.7	9.3	9.0	9.5	9.7	8.7	9.3	9.0	9.5	9.7
	3H	8.6	9.1	8.9	9.3	9.6	8.6	9.1	8.9	9.3	9.6
	4H	8.5	9.0	8.8	9.3	9.6	8.5	9.0	8.8	9.3	9.6
	6H	8.4	8.9	8.8	9.2	9.5	8.4	8.9	8.8	9.2	9.5
	8H	8.4	8.8	8.7	9.1	9.5	8.4	8.8	8.7	9.1	9.5
	12H	8.3	8.7	8.7	9.1	9.4	8.4	8.7	8.7	9.1	9.4
4H	2H	8.5	9.0	8.8	9.3	9.6	8.5	9.0	8.8	9.3	9.6
	3H	8.4	8.8	8.7	9.1	9.4	8.4	8.8	8.7	9.1	9.4
	4H	8.3	8.6	8.7	9.0	9.4	8.3	8.6	8.7	9.0	9.4
	6H	8.2	8.5	8.6	8.9	9.3	8.2	8.5	8.6	8.9	9.3
	8H	8.1	8.4	8.6	8.8	9.3	8.1	8.4	8.6	8.8	9.3
	12H	8.1	8.3	8.5	8.8	9.2	8.1	8.3	8.5	8.8	9.2
8H	4H	8.1	8.4	8.6	8.8	9.3	8.1	8.4	8.6	8.8	9.3
	6H	8.0	8.3	8.5	8.7	9.2	8.0	8.3	8.5	8.7	9.2
	8H	8.0	8.2	8.5	8.6	9.1	8.0	8.2	8.5	8.6	9.1
	12H	7.9	8.1	8.4	8.6	9.1	7.9	8.1	8.4	8.6	9.1
12H	4H	8.1	8.3	8.5	8.8	9.2	8.1	8.3	8.5	8.8	9.2
	6H	8.0	8.2	8.5	8.6	9.1	8.0	8.2	8.5	8.6	9.1
	8H	7.9	8.1	8.4	8.6	9.1	7.9	8.1	8.4	8.6	9.1
Variations with the observer position at spacing:											
S =		1.0H	6.7 / -14.2					6.7 / -14.2			
		1.5H	9.5 / -16.4					9.5 / -16.4			
		2.0H	11.5 / -20.0					11.5 / -20.0			