

Last information update: April 2025

**Product configuration: 6500.01+X660.01**

6500.01: Pole-mounted system - ELL optic - Neutral White - Zhaga Up/Down - White

X660.01: Adapter required for pole-mounted installation for Zhaga version - to be ordered together with the optical assembly - Ø60mm - White



**Product code**

6500.01: Pole-mounted system - ELL optic - Neutral White - Zhaga Up/Down - White

**Technical description**

Outdoor luminaire with direct light street optic. The optical assembly is made of EN1706AC 46100LF aluminium alloy, subjected to a multi-step, pre-treatment process in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The painting stage consists of a primer and a textured acrylic paint, cured at 150 °C, with a high level of weather and UV ray resistance. The 5 mm thick, sodium-calcium closing glass for both optical assemblies is fitted to the product via 3 captive screws on each side. The high IP rating is guaranteed by the silicone gasket placed between the two elements. Product fitted with a double multi-pole Zhaga 4 PIN Up/Down socket. Complete with Neutral White monochrome LED circuit. The wiring and optical assembly can be opened with everyday tools. The light flow emitted in the upper hemisphere of the system in the horizontal position is null (when used with a black finish pole-mounting). Product pre-wired with a 1.1m long outlet cable. The IP68 connector can be purchased separately as an accessory. All external screws are made of stainless steel.

**Installation**

The optical assembly can be installed using two pole-tops that can be ordered separately as an accessory: one for Ø 60mm and one for Ø76mm. It can be installed on Ø102mm pole-tops using a reducer that can be purchased as an accessory.

**Colour**  
White (01)


**Weight (Kg)**  
6.89

**Mounting**  
pole-top

**Wiring**

Connection to be made with an IP68 connector, which can be purchased separately.

Complies with EN60598-1 and pertinent regulations



**Accessory code**

X660.01: Adapter required for pole-mounted installation for Zhaga version - to be ordered together with the optical assembly - Ø60mm - White


**Technical description**

Adapter required for pole-mounted installation for Zhaga version - to be ordered together with the optical assembly - Ø60mm

**Colour**  
White (01)

**Weight (Kg)**  
1.41

Complies with EN60598-1 and pertinent regulations




# Technical data

Im system:	5460	MacAdam Step:	3
W system:	32	Lamp code:	LED
Im source:	5460	Number of lamps for optical assembly:	1
W source:	32	ZVEI Code:	LED
Luminous efficiency (lm/W, real value):	170.6	Number of optical assemblies:	1
Im in emergency mode:	-	Intervall temperatura ambiente:	from -20°C to +35°C. (*)
Total light flux at or above an angle of 90° [Lm]:	11	Power factor:	See installation instructions
Light Output Ratio (L.O.R.) [%]:	100	Inrush current:	21 A / 300 µs
Beam angle [°]:	85° / 110°	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 13 luminaires B16A: 21 luminaires C10A: 21 luminaires C16A: 35 luminaires
CRI (minimum):	70	Minimum dimming %:	10
Colour temperature [K]:	4000	Overvoltage protection:	10kV Common mode & 6kV Differential mode

\* Preliminary data

## Polar



## Isolux

