

Last information update: October 2024

**Product configuration: BQ38**

BQ38: Wall-/Ceiling-mounted - 18 Wram White LEDs - 24V dc - L=1585mm - 32° Flood optic

**Product code**

BQ38: Wall-/Ceiling-mounted - 18 Wram White LEDs - 24V dc - L=1585mm - 32° Flood optic

**Technical description**

Direct light luminaire, designed to use monochrome LED lamps. Ceiling- and wall-mounted. Consists of a body and supports for installation (to be ordered separately). Extruded aluminium body, with zamak die-cast end caps complete with silicone seals. Coated with liquid acrylic paint with a high level of weather and UV ray resistance. The top of the optical assembly is closed by a 3 mm thick transparent glass screen, fixed with silicone. Complete with multi-LED power plate in Wram White 2700K with 24V dc electronic circuit (ballast to be ordered separately); 24V smart driver allowing constant light flow emission despite variations in the input voltage (from 30V dc to 16V dc). Fitted with a PMMA diffusing filter and optic with plastic (methacrylate) lens for 32° FLOOD lighting. All external screws used are made of A2 stainless steel. The luminaire technical characteristics conform to EN 60598-1 standards and particular requirements.

**Installation**

The following accessories are available for installation: adjustable wall-mounted arms in AISI304 stainless steel (L=83mm code BZJ9, 200mm code BZJ8) and a plate for surface- or ceiling-mounting made of anodised aluminium (BZJ7).

**Colour**

Grey (15)

**Mounting**

wall surface|ceiling surface

**Wiring**

The product is supplied with a single nickel-plated brass cable gland PG9 and a 2x1mm<sup>2</sup> PVC and polyurethane outlet cable, 2000mm long. For the electrical connection there is an IP68 linear connector (BZK6) and an IP66 junction box with quick-coupling terminals (BZK7). 24V dc electronic ballasts to be ordered separately: 120W (BZK0), 240W (9912) and 480W (BZK1)

**Notes**

Product complete with LED lamp.

Complies with EN60598-1 and pertinent regulations




IK05

IP66

**Technical data**

Im system:	857	MacAdam Step:	3
W system:	20.8	Life Time LED 1:	100,000h - L80 - B10 (Ta 25°C)
Im source:	1430	Life Time LED 2:	66,000h - L80 - B10 (Ta 40°C)
W source:	20	Voltage [Vin]:	24
Luminous efficiency (Im/W, real value):	41.2	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	60	Number of optical assemblies:	1
Beam angle [°]:	32°	Intervallo temperatura ambiente:	from -30°C to 50°C.
CRI (minimum):	80	LED current [mA]:	350
Colour temperature [K]:	2700	Control:	PWM

Polar



Illuminances

Lux													Wall distance = 1m	
3	0.1	0.2	0.5	1	4	6	4	1	0.5	0.2	0.1			
2	0.2	0.5	1	3	8	14	8	3	1	0.5	0.2			
	0.4	0.8	2	6	17	28	17	6	2	0.8	0.4			
1	0.5	1	3	10	25	37	25	10	3	1	0.5			
	0.7	2	5	12	25	35	25	12	5	2	0.7			
0														
	m	-2	-1	0	1	2	3							