



E821: Pole-mounted system street optic.




Im system:	2630	Lamp code:	LED
W system:	31	Number of lamps for optical assembly:	1
Im source:	-	ZVEI Code:	LED
W source:	-	Number of optical assemblies:	1
Luminous efficiency (lm/W, real value):	84.8	Intervallo temperatura ambiente:	from -40°C to 50°C.
Im in emergency mode:	-	Lifetime of product at ambient operating temperature:	≥ 80.000h Ta=40°C
Total light flux at or above an angle of 90° [Lm]:	29	Power factor:	See installation instructions
Light Output Ratio (L.O.R.) [%]:	100	Inrush current:	31 A / 186 µs
CRI:	70	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 18 luminaires B16A: 30 luminaires C10A: 31 luminaires C16A: 51 luminaires
Colour temperature [K]:	3000	Minimum dimming %:	10
MacAdam Step:	3	Overvoltage protection:	10kV Common mode & 6kV Differential mode
Life Time LED 1:	100,000h - L90 - B10 (Ta 25°C)	Dimming mode:	CCR
Life Time LED 2:	100,000h - L90 - B10 (Ta 40°C)	Control:	DALI
Voltage [Vin]:	230		

# Polar



# Isolux



# Utilisation factors

