

## Laser Blade InOut



Design iGuzzini

iGuzzini

Last information update: April 2025

### Product configuration: E880.S8

E880.S8: Wall-mounted Laser Blade InOut, Warm White LED, Wide Flood optic - Black/Glossy Copper



### Product code

E880.S8: Wall-mounted Laser Blade InOut, Warm White LED, Wide Flood optic - Black/Glossy Copper

### Technical description

Five optic element, outdoor rectangular, wall-mounted luminaire with Warm White LED lamps and a fixed Wide Flood optic. Consists of an optical assembly (rectangular), an upper base, a glass cover, and a wall plate. The optical assembly and upper cover are made of aluminium alloy and are subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The following painting stage consists of a primer and a liquid acrylic paint, cured at 150°C, with a high level of weather and UV ray resistance. Painted plastic cover guard. AISI 304 stainless steel wall fixing plate. The tempered sodium-calcium sealing glass is transparent, with black serigraphy on the edge, 3mm thick and joined to the optical assembly with silicone. There are silicone seals between the upper cover and the optical assembly too. Metallised, thermoplastic, high definition optic, integrated in a rear position in the black, anti-glare screen. Single cable entrance via black polyamide PG11 cable clamp, suitable for  $\varnothing$  6.5÷11mm cables. Connection with three fast-coupling terminals. Possibility to use unipolar cables with 2.4÷3.4mm diameter (1-2,5mm<sup>2</sup>) All external screws used are made of A2 stainless steel.

### Installation

For wall-mounting using the special stainless steel plate. Secure using screw anchors for concrete, cement and solid brick. Product can be installed with the light beam in any direction (up, down, right, left, slanting, etc.).

### Colour

Black/Glossy Copper (S8)

### Weight (Kg)

1.15

### Mounting

wall arm/wall surface

### Wiring

Complete with built-in electronic ballast (220÷240V ac 50/60Hz). Do not use rigid power supply cables.

Complies with EN60598-1 and pertinent regulations



### Technical data

Im system:	670	CRI (minimum):	95
W system:	10	CRI (typical):	97
Im source:	870	Colour temperature [K]:	2700
W source:	10	MacAdam Step:	3
Luminous efficiency (Im/W, real value):	67	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	77	Number of optical assemblies:	1
Beam angle [°]:	47°	Intervallo temperatura ambiente:	from -20°C to +35°C. (*)

\* Preliminary data

### Polar

Imax=1258 cd		C0-180		Lux	
h	d1	d2	Em	Emax	
2	1.7	1.7	256	314	
4	3.4	3.4	64	79	
6	5.2	5.1	28	35	
8	6.9	6.8	16	20	

# Isolux

