



Coefficientes de uso

R	77	75	73	71	55	53	33	00	DRR
K0.8	73	70	67	65	69	66	66	64	78
1.0	76	73	71	69	72	70	70	67	83
1.5	80	78	76	74	77	75	74	72	89
2.0	83	81	79	78	80	78	78	75	93
2.5	84	83	82	81	82	81	80	78	96
3.0	85	84	83	83	83	82	81	79	98
4.0	86	85	85	84	84	84	82	81	99
5.0	87	86	86	86	85	84	83	81	100

Diagrama UGR

Corrected UGR values (at 1200 lm bare lamp luminous flux)											
Reflect.:	ceiling/cav	viewed crosswise					viewed endwise				
		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
work pl.	Room dim	viewed crosswise					viewed endwise				
		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
x	y	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
2H	2H	1.1	1.5	1.3	1.8	2.0	1.1	1.5	1.3	1.8	2.0
	3H	0.9	1.4	1.2	1.6	1.9	0.9	1.4	1.2	1.6	1.9
	4H	0.9	1.3	1.2	1.6	1.8	0.9	1.3	1.2	1.6	1.8
	6H	0.8	1.2	1.1	1.5	1.8	0.8	1.2	1.1	1.5	1.8
	8H	0.8	1.1	1.1	1.4	1.8	0.8	1.1	1.1	1.4	1.8
	12H	0.7	1.1	1.1	1.4	1.7	0.7	1.1	1.1	1.4	1.7
4H	2H	0.9	1.3	1.2	1.6	1.8	0.9	1.3	1.2	1.6	1.8
	3H	0.7	1.1	1.1	1.4	1.7	0.7	1.1	1.1	1.4	1.7
	4H	0.6	0.9	1.0	1.3	1.7	0.6	0.9	1.0	1.3	1.7
	6H	0.5	0.8	1.0	1.2	1.6	0.5	0.8	1.0	1.2	1.6
	8H	0.5	0.7	0.9	1.1	1.6	0.5	0.7	0.9	1.1	1.6
	12H	0.4	0.7	0.9	1.1	1.5	0.4	0.7	0.9	1.1	1.5
8H	4H	0.5	0.7	0.9	1.1	1.6	0.5	0.7	0.9	1.1	1.6
	6H	0.4	0.6	0.9	1.0	1.5	0.4	0.6	0.9	1.0	1.5
	8H	0.3	0.5	0.8	1.0	1.5	0.3	0.5	0.8	1.0	1.5
	12H	0.3	0.4	0.8	0.9	1.4	0.3	0.4	0.8	0.9	1.4
12H	4H	0.4	0.7	0.9	1.1	1.5	0.4	0.7	0.9	1.1	1.5
	6H	0.3	0.5	0.8	1.0	1.5	0.3	0.5	0.8	1.0	1.5
	8H	0.3	0.4	0.8	0.9	1.4	0.3	0.4	0.8	0.9	1.4
Variations with the observer position at spacing:											
S =	1.0H	6.8 / -21.9					6.8 / -21.9				
	1.5H	9.7 / -22.0					9.7 / -22.0				
	2.0H	11.7 / -22.2					11.7 / -22.2				