

iWay round

Design Jean-Michel
Wilmette

iGuzzini


Last information update: February 2025

Product configuration: EN99.15+EP15.15+B513.00

EN99.15: Ø180mm optical assembly - Neutral White LED - 220÷240Vac DALI - Super Comfort 360° optic - 13.1W 714lm - 4000K - Grey

EP15.15: Post for iWay optical compartment Ø170 mm - h = 529 mm - Grey

B513.00: Counter-plate with anchor bolts - Indeterminate



Product code

EN99.15: Ø180mm optical assembly - Neutral White LED - 220÷240Vac DALI - Super Comfort 360° optic - 13.1W 714lm - 4000K - Grey

Technical description

Outdoor, ground or pavement-mounted direct light luminaire, designed to use LED lamps, with a 360° symmetrical optic. The complete product consists of an optical assembly and a cylindrical post to be ordered separately. The optical assembly is made up of various parts, including a top cover made of painted aluminium; a PMMA flux enhancer; a transparent polycarbonate emission lens with an extruded internal bracket and an LED circuit fixed in radial mode; a black-painted, die-cast aluminium cone; a die-cast aluminium lower box for housing the control gear; and silicone seals to guarantee a watertight seal between the top cover, the lens and the cone. The external aluminium parts have been subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The following painting stage consists of a primer and a liquid acrylic paint, cured at 150°C, with a high level of weather and UV ray resistance. At the bottom, the optical assembly is completed by a nickel-plated brass cable clamp and an H07RN-F 4x1mm rubber outlet cable L=1700 mm. The electrical connection requires IP or BOX IP connectors that need to be ordered separately. All external screws used are made of AISI 303 (A1) stainless steel.

Installation

The optical assembly is installed on the lower cylindrical post using a bayonet fitting and secured with two special Torx type screws.

Colour

Grey (15)

Weight (Kg)

1.9


Mounting

ground anchored

Wiring

Electronic control gear unit DALI Vin: 170÷264Vac 164÷264Vdc, 50/60Hz. To adjust the light flow, the control gear can be programmed using a special programming interface (see catalogue) and the output cable from the optical assembly. The control gear is supplied in ON-Off mode and can be transformed into Midnight mode using the interface mentioned above. The DALI driver is compatible with Telemangement systems. An active control system modifies the current intensity to preserve the lifetime of the LEDs under any external ambient temperature conditions.

Complies with EN60598-1 and pertinent regulations



Accessory code

EP15.15: Post for iWay optical compartment Ø170 mm - h = 529 mm - Grey

Technical description

The post is made of aluminium alloy treated with powder paint, which provides a high level of resistance to weather and UV rays. Upper cover made of painted aluminium. Walky optical assembly fixed to post using a single torx-type (safety), stainless steel screw. Inside the post and fixed to the lower base are two stainless steel rods that give the product a high level of impact resistance. The post is anchored to the floor using the fixing base that is made of painted, zinc-plated steel.

Installation

The post can be fastened to the ground/pavement using screw anchors (on pavements) or via a fixing base and plate with anchors that are surface treated with passivation for added protection against corrosion (to be ordered separately).

Colour

Grey (15)

Weight (Kg)

4.5

Mounting

ground surface|ground anchored

Complies with EN60598-1 and pertinent regulations



Accessory code

B513.00: Counter-plate with anchor bolts - Indeterminate


Technical description

Fixing plate with anchor bolts

Colour
Indeterminate (00)

Weight (Kg)
0.5


Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	714	MacAdam Step:	3
W system:	13.1	Life Time LED 1:	100,000h - L80 - B10 (Ta 25°C)
Im source:	2100	Life Time LED 2:	100,000h - L80 - B10 (Ta 40°C)
W source:	11	Lamp code:	LED
Luminous efficiency (Im/W, real value):	54.5	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	7	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	34	Intervallo temperatura ambiente:	from -30°C to 50°C.
CRI (minimum):	80	Control:	DALI-2
Colour temperature [K]:	4000		

Polar



Isolux

