


Last information update: May 2025

Product configuration: ER13+X487.04

ER13: Recessed luminaire Earth D=191 mm - Flush-mount stainless steel frame -Neutral White - Wall Washer Optic - DALI
X487.04: Outer casing in plastic for the ground, floor with stainless steel ring + closure cap - Black

**Product code**

ER13: Recessed luminaire Earth D=191 mm - Flush-mount stainless steel frame -Neutral White - Wall Washer Optic - DALI

Technical description

Recessed luminaire applicable to the floor or ground, designed for fitting monochrome white LED sources, for illumination, fixed optic, with DALI dimmable incorporated electronic control gear. The round frame has a diameter D=191 mm; the body and frame are made of AISI 304 stainless steel with sodium-calcium extra clear glass, thickness 15 mm. Stainless steel body coated with black paint. The luminaire is fixed to the outer casing by means of two TORX-type screws that ensure proper anchoring. Inclusive of LED circuit. The product is wired using an A2 stainless steel cable gland, with type A07RNF 4x1 mm² outgoing power cord having L=1191 mm. The cable is equipped with an anti-transpiration device (IP68) consisting of a silicone seal placed on the power cable and housed inside the product. The outer casing for installation can be ordered separately from the plastic optical assembly. The assembly made up of the frame, optical assembly and outer casing guarantees 5000 kg resistance to static loads. Maximum glass surface temperature is lower than 40°C.

Installation

The product is secured to the outer casing by means of two TORX-type screws. The luminaire can be installed recessed, floor-standing, using an outer casing.

Colour
Steel (13)

Weight (Kg)
3.2

Mounting

Floor recessed|ground recessed


Wiring

Product inclusive of 220-240 VAC DALI dimmable electronic control gear.

Notes

IP68 degree of protection on the product and cable when using IP68 connectors * The product is not suitable for installation in swimming pools and fountains. Overvoltage protection: 4KV Common mode, 3,5KV differenzial mode

Complies with EN60598-1 and pertinent regulations



Complete immersion for limited periods, not suitable for use in swimming pools or fountains.

□ The lighting fixtures were designed and tested to withstand a static load of up to 50000 N and to resist drive-over stress by vehicles with tires. The fixtures cannot be used in lanes subjected to horizontal stresses due to acceleration, braking and / or changes of direction.

Accessory code

X487.04: Outer casing in plastic for the ground, floor with stainless steel ring + closure cap - Black

Technical description

Made of plastic (polypropylene). Inclusive of front cap with system for extracting the cables and double cable entry.

Installation

Floor-standing (concrete)

Colour
Steel (13)

Weight (Kg)
1.4

Mounting

ground surface|Floor recessed|ground recessed

Complies with EN60598-1 and pertinent regulations



Technical data

| | | | |
|--|--------------------------------|--|--|
| Im system: | 779 | Life Time LED 2: | 100,000h - L80 - B10 (Ta 40°C) |
| W system: | 16.5 | Lamp code: | LED |
| Im source: | 1900 | Number of lamps for optical assembly: | 1 |
| W source: | 15 | ZVEI Code: | LED |
| Luminous efficiency (Im/W, real value): | 47.2 | Number of optical assemblies: | 1 |
| Im in emergency mode: | - | Intervallo temperatura ambiente: | from -25°C to 50°C. |
| Total light flux at or above an angle of 90° [Lm]: | 779 | Power factor: | See installation instructions |
| Light Output Ratio (L.O.R.) [%]: | 41 | Inrush current: | 5 A / 50 µs |
| CRI (minimum): | 80 | Maximum number of luminaires of this type per miniature circuit breaker: | B10A: 31 luminaires B16A: 50 luminaires C10A: 52 luminaires C16A: 85 luminaires |
| Colour temperature [K]: | 4000 | Minimum dimming %: | 1 |
| MacAdam Step: | 2 | Overvoltage protection: | 4kV Common mode & 3kV Differential mode |
| Life Time LED 1: | 100,000h - L90 - B10 (Ta 25°C) | Control: | DALI-2 |

Polar