


Last information update: April 2025

Product configuration: EW12

EW12: Pole-mounted system – ST1.5 optic - Warm White - ø46-60-76mm

**Product code**

EW12: Pole-mounted system – ST1.5 optic - Warm White - ø46-60-76mm

Technical description

Outdoor luminaire with direct light street optic, designed to use LED lamps. The optical assembly and the pole attachment system are made of EN1706AC 46100LF aluminium alloy and subjected to a multi-step, pre-treatment process, in which the main phases are: degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The painting stage consists of a primer and a textured liquid acrylic paint, cured at 150 °C, with a high level of weather and UV ray resistance. Option of adjusting the inclination in relation to the road surface by +20°/-5° (in 5° steps) for a pole-top installation and +5°/20° (in 5° steps) for a lateral installation. 5 mm thick extra-clear sodium-calcium closure glass fastened to the product with 4 screws. The high IP rating is guaranteed by the silicone gasket placed between the two elements. Electronic power supply with 100%-70% Middle of the Night profile. Driver with automatic internal temperature control system. Wiring and optical compartment can be opened with common tools. The luminous flux emitted in the upper hemisphere of the system in the horizontal position is null (in conformity with the strictest standards for the prevention of light pollution). All external screws are made of stainless steel.

Installation

The spotlight can be installed with a pole-top or lateral mounting.

Colour

Grey (15)

Weight (Kg)

9.8

Mounting

wall arm|pole-top

Notes

In the event of installations on insulated supports (like fibreglass poles) it is mandatory (or strongly recommended) to use the accessory code X899 to protect the luminaire from eventual faults due to electrostatic charges.

Complies with EN60598-1 and pertinent regulations

**Technical data**

Im system:	15530.0	MacAdam Step:	3
W system:	110.4	Life Time LED 1:	100,000h - L90 - B10 (Ta 25C)
Im source:	15530	Life Time LED 2:	100,000h - L80 - B10 (Ta 25C)
W source:	102	Voltage [Vin]:	230
Luminous efficiency (lm/W, real value):	140.67	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0.0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	100	Number of optical assemblies:	1
Beam angle [°]:	146° / 66°	Intervallo temperatura ambiente:	from -40°C to 35°C.
CRI:	70	Control:	Midnight preset/DALI NFC
Colour temperature [K]:	3000		