

Last information update: July 2024



**Accessory code**

MY83: Constant current power supply unit 1-10V IP20 50W - VIN = 220-240VAC 50/60Hz Ø25

**Technical description**

Dimmable 1-10V electronic ballast - constant current operation. Protection devices: thermal/short circuit - mains overvoltage - overloads.

**Installation**

remote installation - including securing slots with screws.

**Colour**

Indeterminate (00)

**Weight (Kg)**

0.21

**Dimension (mm) (\*)**

124x79x22

\* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.

**Wiring**

700 mA for Ø25 Laser recessed luminaires - min 2 - max 20 used. Palco Recessed-Surface - Ø19 / 700 mA max 22 - Ø37 / 650 mA max 5 - Ø51 / 1050 mA max 3. Cables secured with quick connection terminals.

Complies with EN60598-1 and pertinent regulations



**Technical data**

Frequency [Hz]:	0/50/60	Maximum number of LED power supply units of this type per miniature circuit breaker:	B10A: 9 power supply units B16A: 15 power supply units C10A: 15 power supply units C16A: 25 power supply units
Current out [mA]:	350		
Inrush current:	20 A / 400 µs	Overvoltage protection:	4kV Common mode & 4kV Differential mode