


Last information update: April 2025

Product configuration: N017

N017: Fixed circular recessed luminaire - Ø242 mm - neutral white - flood optic - UGR<19

**Product code**N017: Fixed circular recessed luminaire - Ø242 mm - neutral white - flood optic - UGR<19 **Attention! Code no longer in production****Technical description**

Fixed round luminaire designed to use a LED lamp with C.O.B. technology. Version with rim for surface-mounting. Reflector vacuum-metallised with aluminium vapours with an anti-scratch protective layer. Structure with die-cast aluminium perimeter frame, black, zinc-plated sheet steel brackets and extruded aluminium dissipater painted black. Passive dissipation system. Product complete with LED lamp in neutral white colour tone (4,000K). General light emission, with controlled luminance UGR<19 1500 cd/m² α>65° flood optic.

Installation

Recessed using torsion springs which allow easy installation in false ceilings with thickness ranging from 1 mm to 25 mm.

Colour

White / Aluminium (39)

Weight (Kg)

2.46

Mounting

ceiling recessed

Wiring

product complete with an electronic ballast

Notes

TPa rated

Complies with EN60598-1 and pertinent regulations

**Technical data**

Im system:	6213.96	CRI:	80
W system:	55.4	Colour temperature [K]:	4000
Im source:	8200	MacAdam Step:	2
W source:	49	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25C)
Luminous efficiency (Im/W, real value):	112.17	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0.0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	76	Number of optical assemblies:	1
Beam angle [°]:	24°		