

Last information update: February 2025

Product configuration: N203.00+LENGTH5

N203.00: Flexible strip - 5m - white LEDs. - 19.2W 1900lm (1.0 m) - 2700K - CRI 90 - Indeterminate
 LENGTH5: Length (m) - 5m

**Product code**

N203.00: Flexible strip - 5m - white LEDs. - 19.2W 1900lm (1.0 m) - 2700K - CRI 90 - Indeterminate

Technical description

Product for linear lighting – fitted with monochromatic white LEDs with high colour rendering – assembled on white flexible circuit; transparent silicone sheath outer protection with end caps. IP65 protection rating for the full-length strip (undivided). The circuit ends include connectors with IP20 protection rating, therefore the installer is responsible for adapting the insulation level of the connectors. Supplied in 5-metre coils wound on special supports; supplied with a connection kit for connections in line or to power supply. The strip can be cut into 125mm-long sections; in case of intermediate cuts, ensure that the cut ends are carefully sealed so that the original protection conditions are restored. LED characteristics: White 2700K - CRI 90 - SDCM 3 - 56 LEDs/m - 112° beam angle - 96 W in total - 24V power supply. Control gears to be ordered separately.

Installation

Fixing kit: clips (code MWG2: 10 pieces) and rigid aluminium support (code MWG1: 5 pieces x 1 m) - The strip is configured for being combined with all Underscore 15 profiles.

Colour
 White (01)

Weight (Kg)
 0.21

Mounting

wall arm|ceiling surface

Wiring

Constant voltage ballast ordered separately; available for single coil (ON-OFF code MZ14 / DALI dimmable code MZ15). The control gear and coil are connected through connectors (IP20) supplied with the strip package.

Notes

To ensure correct heat dissipation, the strip should be used in conjunction with the available profiles. The relevant connectors guarantee an IP20 protection rating. If the strip is cut (at the configured points), ensure that the various parts are carefully sealed once they have been joined together.

Complies with EN60598-1 and pertinent regulations



IP20

IP65

if the strip
is uncut

**Technical data**

Im system:	9500	Colour temperature [K]:	2700
W system:	96	MacAdam Step:	3
Im source:	1900	Life Time LED 1:	> 50,000h - L70 (Ta 25°C)
W source:	19.2	Voltage [Vin]:	24
Luminous efficiency (Im/W, real value):	99	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	401	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	100	Number of optical assemblies:	5
CRI (minimum):	90		

Polar

Imax=656 cd		Lux			
90°	180°	h	d	Em	Emax
		2	5.9	95	164
		4	11.8	24	41
		6	17.7	11	18
		8	23.6	6	10
α = 112°					

Isolux

