



Product configuration: P131

P131: 5 - cell Recessed luminaire - LED - Warm white - Incorporated DALI dimmable power supply - Spot optic



P131: 5 - cell Recessed luminaire - LED - Warm white - Incorporated DALI dimmable power supply - Spot optic

rectangular miniaturised recessed luminaire with 5 optical elements with LED lamps - fixed optics - spot beam angle. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. Metallised thermoplastic high definition optics, integrated in a rear position in the black anti-glare screen; the structure of the optical system prevents a pinpoint effect, allowing precise, circular light distribution and emission with controlled glare . Supplied with DALI dimmable electronic control gear connected to the luminaire. Warm white high colour rendering LED.

recessed with steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 37 x 141

White (01) | Black / Black (43) | Black / White (47) | White/Gold (41)* | Grey / Black (74)* | White / burnished chrome (E7)*

* Colours on request

0.3

wall recessed|ceiling recessed

on control gear box; screw connections with terminal block included

Complies with EN60598-1 and pertinent regulations



Im system:	671.5	CRI:	95
W system:	13.0	Colour temperature [K]:	2700
Im source:	850	MacAdam Step:	3
W source:	10	Life Time LED 1:	50,000h - L90 - B10 (Ta 25C)
Luminous efficiency (Im/W, real value):	51.65	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0.0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	79	Number of optical assemblies:	1
Beam angle [°]:	12°	Control:	DALI-2