


Last information update: November 2024

Product configuration: P309.01

P309.01: Fixed round mini-recessed luminaire - LED - spot - White

**Product code**

P309.01: Fixed round mini-recessed luminaire - LED - spot - White

Technical description

Fixed round mini-recessed luminaire with contact frame. The LED is set back to minimize direct glare. The recessed body is made of machined aluminium and the inside of the ring of thermoplastic available in a range of painted and metallised finishes. PMMA - spot (16°) high resolution optic lens. High color rendering index 2700K LED. Tool free assembly. Power unit available with a separate code no.

Installation

Recessed in a false ceiling by means of a steel wire spring - minimum thickness of false ceiling: 1 mm - preparation hole Ø 25 mm.

Colour

White (01)

Weight (Kg)

0.03

Mounting

wall recessed|ceiling recessed

Wiring


Direct current ballasts are available with a separate code no.: ON-OFF / 1-10V dimmable / DALI dimmable / Trailing Edge dimmable

Complies with EN60598-1 and pertinent regulations



IP20

IP43

On the visible part of
the product once installed**Technical data**

lm system:	115	CRI (minimum):	90
W system:	2	Colour temperature [K]:	2700
lm source:	180	MacAdam Step:	2
W source:	2	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	57.6	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	64	Number of optical assemblies:	1
Beam angle [°]:	14°	LED current [mA]:	700

Polar

Imax=1264 cd		Lux			
90°	180°	90°	h	d	Em Emax
			1	0.2	967 1264
			2	0.5	242 316
			3	0.7	107 140
			4	1	60 79
$\alpha = 14^\circ$					

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	57	53	51	49	53	51	50	48	75
1.0	59	56	54	52	56	54	53	51	80
1.5	62	60	58	57	59	58	57	55	86
2.0	65	63	62	60	62	61	60	58	91
2.5	66	65	64	63	64	63	62	60	94
3.0	67	66	65	64	65	64	63	62	96
4.0	68	67	66	66	66	65	64	63	98
5.0	68	68	67	67	66	66	65	63	99

Luminance curve limit

