



Last information update: May 2025

Product configuration: P325

P325: Adjustable (tilting) round recessed luminaire - LED - flood

**Product code**

P325: Adjustable (tilting) round recessed luminaire - LED - flood

Technical description

Round recessed luminaire with contact frame. Adjustable version that tilts by a maximum of 30°. The main swivel body is made of die-cast aluminium with a radiant surface that guarantees optimum heat dissipation. Metallised, thermoplastic, high definition reflector - flood optic. Structure with die-cast aluminium external contact frame with a single white finish. Steel rotating parts. The ring inside the swivel body is made of thermoplastic available in a range of painted and metallised finishes. Safety glass included Quick and easy tool free assembly. High color rendering index 2700K LED. Power unit available with a separate code no.

Installation

Recessed in a false ceiling by means of an anti-fall steel wire spring - minimum thickness of false ceiling: 1 mm - preparation hole Ø 59 mm.

Colour

White (01) | Black / Black (43) | Black / White (47) | White/Gold (41)* | White / Chrome (E4)* | White / burnished chrome (E7)* | White / gold satin-finish (E9)*

Weight (Kg)

0.13

* Colours on request

Mounting

wall recessed/ceiling recessed

Wiring

Direct current ballasts are available with a separate code no.: ON-OFF / 1-10V dimmable / DALI dimmable / Trailing Edge dimmable - the recessed fitting includes a cable and a quick-coupling connector to connect it to the connector on the ballast.

Notes

To reduce the glare caused by the internal wall of the recess when the luminaire has been rotated, a black, snap on accessory ring is available. A wide range of decorative accessories and diffusers is also available.

Complies with EN60598-1 and pertinent regulations



IP20

IP23

On the visible part of the product once installed

**Technical data**

Im system:	616	CRI (minimum):	90
W system:	6.8	Colour temperature [K]:	2700
Im source:	760	MacAdam Step:	2
W source:	6.8	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	90.5	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	81	Number of optical assemblies:	1
Beam angle [°]:	40°	LED current [mA]:	200

Polar

	Lux			
	h	d	Em	Emax
	1	0.7	1161	1500
	2	1.5	290	375
	3	2.2	129	167
	4	2.9	73	94

CIE
nL 0.81
98-100-100-100-81
UGR 10.1-10.2

DIN
A.61


UTE
0.81A+0.00T
F*1=984
F*1+F*2=998
F*1+F*2+F*3=1000

CIBSE
LG3 L<3000 cd/m² at 65°
UGR<16 | L<3000 cd/mq @ 65°

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	73	69	66	64	68	66	65	63	77
1.0	76	72	70	68	72	69	69	66	82
1.5	80	77	75	73	76	74	74	71	88
2.0	82	80	79	78	79	78	77	75	92
2.5	84	82	81	80	81	80	79	77	95
3.0	85	84	83	82	83	82	81	79	97
4.0	86	85	85	84	84	83	82	80	99
5.0	86	86	85	85	85	84	83	81	100

Luminance curve limit



UGR diagram

Corrected UGR values (at 700 lm bare lamp luminous flux)											
Reflect.: ceiling/cav walls work pl. Room dim x y		viewed crosswise					viewed endwise				
		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
2H	2H	10.5	11.1	10.8	11.3	11.6	10.5	11.1	10.8	11.3	11.6
	3H	10.5	11.0	10.8	11.3	11.5	10.5	11.0	10.8	11.3	11.5
	4H	10.4	10.9	10.7	11.2	11.5	10.4	10.9	10.7	11.2	11.5
	6H	10.3	10.8	10.7	11.1	11.4	10.3	10.8	10.7	11.1	11.4
	8H	10.3	10.7	10.7	11.0	11.4	10.3	10.7	10.7	11.1	11.4
	12H	10.3	10.7	10.6	11.0	11.4	10.3	10.7	10.6	11.0	11.4
4H	2H	10.4	10.9	10.7	11.2	11.5	10.4	10.9	10.7	11.2	11.5
	3H	10.4	10.8	10.7	11.1	11.5	10.3	10.8	10.7	11.1	11.4
	4H	10.3	10.6	10.7	11.0	11.4	10.3	10.6	10.7	11.0	11.4
	6H	10.2	10.5	10.6	10.9	11.3	10.2	10.5	10.6	10.9	11.3
	8H	10.1	10.4	10.6	10.8	11.3	10.2	10.4	10.6	10.9	11.3
	12H	10.1	10.4	10.5	10.8	11.2	10.1	10.4	10.6	10.8	11.2
8H	4H	10.2	10.4	10.6	10.9	11.3	10.1	10.4	10.6	10.8	11.3
	6H	10.1	10.3	10.5	10.7	11.2	10.1	10.3	10.5	10.7	11.2
	8H	10.0	10.2	10.5	10.7	11.2	10.0	10.2	10.5	10.7	11.2
	12H	10.0	10.1	10.5	10.6	11.1	10.0	10.1	10.5	10.6	11.1
12H	4H	10.1	10.4	10.6	10.8	11.2	10.1	10.4	10.5	10.8	11.2
	6H	10.0	10.2	10.5	10.7	11.2	10.0	10.2	10.5	10.7	11.2
	8H	10.0	10.1	10.5	10.6	11.1	10.0	10.1	10.5	10.6	11.1
Variations with the observer position at spacing:											
S =	1.0H	5.0 / -5.1					5.0 / -5.1				
	1.5H	7.7 / -7.5					7.7 / -7.5				
	2.0H	9.7 / -9.9					9.7 / -9.9				