



Design iGuzzini iGuzzini

Product configuration: P780.74

P780.74: Fixed recessed luminaire - Warm LED - DALI dimmable control gear - Medium - Grey / Black



P780.74: Fixed recessed luminaire - Warm LED - DALI dimmable control gear - Medium - Grey / Black

Fixed optic, recessed luminaire for a Warm White LED lamp with a high color rendering index. Passive heat dissipation system. Lamp body with die-cast aluminium radiant surface, version with perimeter surface frame. Metallised, thermoplastic, high definition Opti Beam optic, integrated in a set-back position in the anti-glare screen. Glass cover for LED lamp. The structure of the optic system produces light emission with controlled luminance ($UGR < 19$) to guarantee high visual comfort. Supplied with a dimmable DALI ballast connected to the luminaire.

Recessed with steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 125 x 125. Installation possible in a horizontal position.

0.86

ceiling recessed

Quick-coupling connections on the ballast unit terminal block - Digital electronic cabling that allows dimming to be performed with DALI protocol or pushbutton systems (TOUCH DIM)

The product has a white finish (01) that maintains its UGR < 19 performance unaltered even when luminance values vary slightly.

Complies with EN60598-1 and pertinent regulations



Im system:	2243	CRI (minimum):	90
W system:	32.1	Colour temperature [K]:	2700
Im source:	3250	MacAdam Step:	2
W source:	28	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	69.9	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	69	Number of optical assemblies:	1
Beam angle [°]:	22°	Control:	DALI

	CIE nL 0.69 100-100-100-100-69 UGR <10-<10		Lux			
	DIN A.61		h	d	Em	Emax
	UTE 0.69A+0.00T F*1=999 F*1+F*2=1000 F*1+F*2+F*3=1000		2	0.7	2357	2992
	CIBSE LG3 L<1500 cd/m² at 65° UGR<10 L<1500 cd/mq @65°		4	1.5	589	748
			6	2.2	262	332
			8	3	147	187

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	62	59	57	55	59	57	56	54	78
1.0	65	62	60	59	62	60	59	57	83
1.5	68	66	64	63	65	64	63	61	89
2.0	70	69	68	66	68	67	66	64	93
2.5	72	70	70	69	70	69	68	66	96
3.0	73	72	71	70	71	70	69	67	98
4.0	73	73	72	72	72	71	70	69	99
5.0	74	73	73	73	72	72	71	69	100

UGR diagram

Corrected UGR values (at 3250 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceiling/cav		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim											
x	y										
2H	2H	6.2	8.3	6.6	8.6	8.9	6.2	8.3	6.6	8.6	8.9
	3H	6.1	7.6	6.5	7.9	8.3	6.1	7.6	6.5	7.9	8.3
	4H	6.0	7.3	6.4	7.6	8.0	6.0	7.3	6.4	7.6	8.0
	6H	6.0	7.0	6.3	7.3	7.7	6.0	7.0	6.3	7.3	7.7
	8H	5.9	7.0	6.3	7.3	7.7	5.9	7.0	6.3	7.3	7.7
	12H	5.9	6.9	6.3	7.3	7.7	5.9	6.9	6.3	7.3	7.7
4H	2H	6.0	7.3	6.4	7.6	8.0	6.0	7.3	6.4	7.6	8.0
	3H	5.9	6.9	6.3	7.3	7.7	5.9	6.9	6.3	7.3	7.7
	4H	5.7	6.8	6.1	7.2	7.6	5.7	6.8	6.1	7.2	7.6
	6H	5.4	7.0	5.9	7.5	8.0	5.4	7.0	5.9	7.5	8.0
	8H	5.3	7.1	5.8	7.6	8.1	5.3	7.1	5.8	7.6	8.1
	12H	5.2	7.1	5.7	7.5	8.1	5.2	7.1	5.7	7.5	8.1
8H	4H	5.3	7.1	5.8	7.6	8.1	5.3	7.1	5.8	7.6	8.1
	6H	5.1	6.9	5.7	7.4	7.9	5.1	6.9	5.7	7.4	7.9
	8H	5.1	6.6	5.7	7.1	7.7	5.1	6.6	5.7	7.1	7.7
	12H	5.3	6.2	5.8	6.7	7.2	5.3	6.2	5.8	6.7	7.2
12H	4H	5.2	7.1	5.7	7.5	8.1	5.2	7.1	5.7	7.5	8.1
	6H	5.1	6.6	5.7	7.1	7.7	5.1	6.6	5.7	7.1	7.7
	8H	5.3	6.2	5.8	6.7	7.2	5.3	6.2	5.8	6.7	7.2
Variations with the observer position at spacing:											
S =		1.0H	7.0 / -23.7				7.0 / -23.7				
		1.5H	9.8 / -24.0				9.8 / -24.0				
		2.0H	11.8 / -24.3				11.8 / -24.3				