

DALI IP20 20W constant current power supply unit - for 1 Crystal HO Tunable White recessed luminaire

Design iGuzzini

iGuzzini

Last information update: January 2025



Accessory code

PD83: DALI IP20 20W constant current power supply unit - for 1 Crystal HO Tunable White recessed luminaire

Technical description

DALI 20W dimmable constant current electronic power supply.

Can be used for HO Tunable White models.

Input $V_{in}=220\div240$ Vac 50÷60Hz.

SELV output.

The product features include common mode and differential mode overvoltage protection, short circuit protection, overcurrent and overtemperature protection.

Installation

Compatible with opening for Crystal recessed fitting assembly.

Colour

Indeterminate (00)

Weight (Kg)

0.23

Dimension (mm) (*)

120x51x29.2

* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.

Wiring

The power supply is fitted with a cable and quick-coupling connector for facilitating a direct connection to the recessed fitting.

Primary and secondary cable clamp.

Notes

DT8 type DALI check. 1 address, 1 DALI load (2 mA)

Complies with EN60598-1 and pertinent regulations



IP20



Technical data

Frequency [Hz]: 0/50/60

Current out [mA]: 300

Inrush current: 29 A / 153 μ s

Maximum number of LED power supply units of this type per miniature circuit breaker:

B10A:	32 power supply units
B16A:	51 power supply units
C10A:	53 power supply units
C16A:	86 power supply units

Minimum dimming %: 1

Overvoltage protection: 2kV Common mode & 1kV Differential mode

Control: DALI-2