


Last information update: April 2025

Product configuration: PV85

PV85: Robin spotlight Ø51 for installation on a 48V low voltage track - DALI Powerline



Product code

PV85: Robin spotlight Ø51 for installation on a 48V low voltage track - DALI Powerline

Technical description

Miniaturised adjustable spotlight with adapter for installation on a 48V Filorail low voltage track. The thermoplastic adapters are designed so they can be installed even in the curved track sections. Die-cast aluminium body with an ideal passive dissipation system to guarantee a long life and effective heat management. Driver circuit with DALI Powerline technology that allows each spotlight on the track to be adjusted independently. This offers a remarkable level of flexibility and lighting control. The swivel joints allow the spotlight to be rotated by 360° and tilted by 160°. The set back position of the optic unit guarantees a high level of visual comfort. A high definition thermoplastic lens with the option of using additional accessories to create other light effects. A rapid tool-free system for connecting the adapter electrically and mechanically to the track.

Installation

On a low voltage Filorail track. A tool-free system for connecting the product electrically and mechanically to the track.

Colour

White (01) | Black (04)

Weight (Kg)

0.45

Wiring

LED driver integrated in product body - direct connection on 48V track. Track power supply unit to be ordered separately.

Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	1260.01	MacAdam Step:	2
W system:	18.0	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25C)
Im source:	1640	Voltage [Vin]:	48
W source:	17	Lamp code:	LED
Luminous efficiency (Im/W, real value):	70.0	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0.0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	77	Power factor:	See installation instructions
Beam angle [°]:	15°	Overvoltage protection:	0kV Common mode & 0kV Differential mode
CRI:	90	Control:	DALI
Colour temperature [K]:	3000		