


Product configuration: PX50.01

PX50.01: Floodlight with base – Neutral White – Integrated power supply - DALI-2 - 28.6W 3260lm - 4000K - White



PX50.01: Floodlight with base – Neutral White – Integrated power supply - DALI-2 - 28.6W 3260lm - 4000K - White

Floodlight designed to use LED lamps and an STCy0.5 optic. Consisting of an optical assembly, an arm with a swivel joint and a glass-holding frame and base in aluminium alloy, subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation and sealing. The following painting stage consists of a primer and a liquid acrylic paint, cured at 150°C, with a high level of weather and UV ray resistance. Transparent, 4mm thick, tempered sodium-calcium closing glass. The gasket is in black silicone. The product includes a Neutral White monochrome circuit with a Black Optismart Lens optical system. The electronic DALI-2 power supply is integrated in the product and compatible with remote management systems. The frame includes steel retaining cables. The product with a base can be adjusted on a vertical plane by $\pm 45^\circ$ and on a horizontal plane by 360° . All external screws used are made of A2 stainless steel.

The product can be floor, wall or ceiling-installed and also pole-mounted using steel arms or a steel flange.

White (01)

3.67

wall arm | wall surface | ceiling surface

Complies with EN60598-1 and pertinent regulations



lm system:	3260
W system:	28.6
lm source:	-
W source:	-
Luminous efficiency (lm/W, real value):	114
lm in emergency mode:	-
Total light flux at or above an angle of 90° [Lm]:	0
Light Output Ratio (L.O.R.) [%]:	100
CRI (minimum):	80
Colour temperature [K]:	4000
MacAdam Step:	3
Life Time LED 1:	100,000h - L90 - B10 (Ta 25°C)

Life Time LED 2:	100,000h - L90 - B10 (Ta 40°C)
Lamp code:	LED
Number of lamps for optical assembly:	1
ZVEI Code:	LED
Number of optical assemblies:	1
Intervallo temperatura ambiente:	from -40°C to 50°C.
Power factor:	See installation instructions
Inrush current:	21 A / 300 µs
Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 13 luminaires B16A: 21 luminaires C10A: 21 luminaires C16A: 35 luminaires
Overvoltage protection:	10kV Common mode & 6kV Differential mode
Control:	DALI-2