

Last information update: November 2024

#### Product configuration: QA86+QB42.01

QA86: Initial moduleFrame DownGeneral LightL 2397

QB42.01: Down HO plate - ON-OFF - General Light - LED Neutral - L 1196 - 24.5W 3015lm - 4000K - White



#### Product code

QA86: Initial moduleFrame DownGeneral LightL 2397

#### Technical description

Initial profile in extruded aluminium - Frame version with contact frame; methacrylate opal screen for diffused general light; screen set up for connecting several lengths by overlapping.

#### Installation

Recessed using the brackets on the profile. The initial modules can be used individually (stand-alone), if completed with accessory caps and the required LED module.

#### Colour

White (01)

#### Weight (Kg)

5

#### Mounting

ceiling recessed/ceiling pendant

#### Wiring

Set up to house the LED modules required by the system.

#### Notes

Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.

TPb rated. TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations



#### Product code

QB42.01: Down HO plate - ON-OFF - General Light - LED Neutral - L 1196 - 24.5W 3015lm - 4000K - White **Attention! Code no longer in production**

#### Technical description

LED module set up for housing in initial or intermediate system profiles. Down emission - High Output version for General Light profiles (with opal diffuser screen). The module optic and structural fittings allow high luminous flux and system efficiency values. Electronic control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Neutral 4000K LED

#### Installation

Module insertion on profiles facilitated by a quick coupling system.

#### Colour

Indeterminate (00)

#### Weight (Kg)

1.28

#### Wiring

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated ON-OFF - non-dimmable control gear.

Complies with EN60598-1 and pertinent regulations



#### Technical data

lm system:	6308	CRI (minimum):	80
W system:	49.2	Colour temperature [K]:	4000
lm source:	8300	MacAdam Step:	3
W source:	44	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	128.2	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	76	Number of optical assemblies:	1

Polar

