

Last information update: November 2024

Product configuration: QA88+QB49.01

QA88: Module for continuous lineFrame DownGeneral LightL 898

QB49.01: Down HO plate - ON-OFF - General Light - LED Warm - L 896 - 18.5W 2135lm - 3000K - White

**Product code**

QA88: Module for continuous lineFrame DownGeneral LightL 898

Technical description

Extruded aluminium intermediate profile - Frame version with contact frame; this allows continuous lines to be created with other intermediate profiles and an initial profile (required). Methacrylate opal screen for diffused general light; screen set up for connecting several lengths by overlapping.

Installation

This can be recessed using the brackets on the profile; the mechanical systems for connecting the subsequent profiles are included in the package.

Colour

White (01)

Weight (Kg)

1.86

Mounting

ceiling recessed|ceiling pendant

Wiring

Set up to house the LED modules required by the system.

Notes

Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.

TPb rated. TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations

**Product code**

QB49.01: Down HO plate - ON-OFF - General Light - LED Warm - L 896 - 18.5W 2135lm - 3000K - White **Attention! Code no longer in production**

Technical description

LED module set up for housing in initial or intermediate system profiles. Down emission - High Output version for General Light profiles (with opal diffuser screen). The module optic and structural fittings allow high luminous flux and system efficiency values. Electronic control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Warm 3000K LED

Installation

Module insertion on profiles facilitated by a quick coupling system.

Colour

Indeterminate (00)

Weight (Kg)

0.99

Wiring

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated ON-OFF - non-dimmable control gear.

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system: 2204

W system: 18.6

lm source: 2900

W source: 17

Luminous efficiency (lm/W, 118.5

real value):

lm in emergency mode: -

Total light flux at or above 0

an angle of 90° [Lm]:

Light Output Ratio (L.O.R.) 76

[%]:

CRI (minimum): 80

Colour temperature [K]: 3000

MacAdam Step: 3

Life Time LED 1: > 50,000h - L90 - B10 (Ta 25°C)

Lamp code: LED

Number of lamps for optical 1

assembly:

ZVEI Code: LED

Number of optical 1

assemblies:

Polar

