

Last information update: November 2024

Product configuration: QB54+QZ58.01

QB54: Down HO plate - DALI - General Light - LED Warm - L 1196

QZ58.01: Initial module - Minimal Down - General Light - L 1208 - TP(a) - White

Product code

QB54: Down HO plate - DALI - General Light - LED Warm - L 1196

Technical description

LED module set up for housing in initial or intermediate system profiles. Down emission - High Output version for General Light profiles (with opal diffuser screen). The module optic and structural fittings allow high luminous flux and system efficiency values. DALI dimmable control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Warm 3000K LED

Installation

Module insertion on profiles facilitated by a quick coupling system.

Colour

Indeterminate (00)

Weight (Kg)

1.28

Wiring

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable digital DALI control gear.

Complies with EN60598-1 and pertinent regulations



Product code

QZ58.01: Initial module - Minimal Down - General Light - L 1208 - TP(a) - White

Technical description

Initial profile in extruded aluminium - Minimal (frameless) version for flush with ceiling installation; polycarbonate screen for diffused general light in compliance with the TP(a) standard; screen set up for connecting several lengths by overlapping.

Installation

Installation can be recessed, surface, ceiling and pendant-mounted using suitable accessories to be ordered separately. The initial modules can be used individually for various applications if completed with accessory caps and the required LED module.

Colour

White (01)

Weight (Kg)

2.35

Mounting

ceiling recessed|ceiling surface|ceiling pendant

Wiring

Set up to house the LED modules required by the system.

Notes


Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.

Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	2457	CRI (minimum):	80
W system:	22	Colour temperature [K]:	3000
Im source:	3900	MacAdam Step:	3
W source:	22	Lamp code:	LED
Luminous efficiency (Im/W, real value):	111.7	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	63	Control:	DALI-2



Polar

