


Palco Recessed / Surface

Last information update: October 2024

Product configuration: QC13
QC13: Palco single recess Ø19 - medium - remote driver



Product code
QC13: Palco single recess Ø19 - medium - remote driver

Technical description
Miniaturised adjustable spotlight for recessed installation. Spotlight body with a cast zamak dissipation system and rotation units - machined aluminium recess base - steel wire fixing springs. The swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic unit guarantees a high level of visual comfort with a thermoplastic high definition lens. Ballast not included, available with separate code.


Installation
Recessed base with surface stop plate - steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole Ø19 mm.

Colour	Weight (Kg)
White (01) Black (04)	0.06

Mounting
wall recessed|ceiling recessed

Wiring
Output cables for connecting to power supply line.

Complies with EN60598-1 and pertinent regulations



Technical data			
Im system:	121	CRI (minimum):	90
W system:	2	Colour temperature [K]:	2700
Im source:	180	MacAdam Step:	2
W source:	2	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	60.3	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	67	Number of optical assemblies:	1
Beam angle [°]:	24°	LED current [mA]:	700

