

Last information update: December 2024

#### Product configuration: QH86+R410.01

QH86: Plate - General Down Light - DALI - Neutral LED - L 3588

R410.01: Frame initial module - General Down Light - L 3594 - TP(a) - White



#### Product code

QH86: Plate - General Down Light - DALI - Neutral LED - L 3588

#### Technical description

LED module set up for housing in initial or intermediate system profiles, ideal for particularly long light lines. Emission for General Light profiles (with opal diffuser screen). DALI dimmable electronic control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Neutral 4000K LED

#### Installation

Module insertion on profiles facilitated by a quick coupling system.

#### Colour

Indeterminate (00)

#### Weight (Kg)

4.1


#### Wiring

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable DALI control gear.

#### Notes

Important: the triple length intermediate luminous module can be used for both initial profiles - L 3594 - for stand-alone applications, and intermediate profiles - L 3594 - for continuous line applications.

Complies with EN60598-1 and pertinent regulations



#### Product code

R410.01: Frame initial module - General Down Light - L 3594 - TP(a) - White

#### Technical description

Initial profile in extruded aluminium - Frame version with contact frame; methacrylate opal screen (diffused general light) in compliance with the TP(a) standard; screen set up for connecting several lengths by overlapping.

#### Installation

Recessed using the brackets on the profile. The initial modules can be used individually if completed with accessory caps and the required LED module.

#### Colour

White (01)\*

#### Weight (Kg)

1.9

\* Colours on request

#### Mounting

ceiling recessed


#### Wiring

Set up to house the LED modules required by the system.

#### Notes

Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.


Complies with EN60598-1 and pertinent regulations



#### Technical data

Im system:	9920	Colour temperature [K]:	4000
W system:	101.2	MacAdam Step:	3
Im source:	16000	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W source:	90	Voltage [Vin]:	230
Luminous efficiency (Im/W, real value):	98	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	62	Number of optical assemblies:	1
CRI (minimum):	80	Control:	DALI-2

# Polar



# Isolux

