

## Blade R downlight


Design iGuzzini

iGuzzini

Last information update: January 2025

**Product configuration: QS69**

QS69: Minimal Ø 84 - Flood beam - LED



## Product code

Product code  
QS69: Minimal Ø 84 - Flood beam - LED

### Technical description

Ring luminaire with 6 optical elements for LED lamps - fixed optics. The optic system guarantees a high level of visual comfort and no glare. The body includes a radiant surface made of die-cast aluminium. Minimal (frameless) version for flush with ceiling installation. For recessed installation in a false ceiling a specific adapter is required that is available with a separate item code. High definition reflectors made of thermoplastic material vacuum-metallised with aluminium vapours, integrated in a set-back position in the anti-glare screen. Supplied with a power supply unit connected to the luminaire. Central cover available with separate item code.

## Installation

Recessed with steel wire springs for false ceilings from 12.5 to 25 mm thick - Ø 84 installation hole.

**Colour**

White (01) | Black (04) | Gold (14)\* | Burnished chrome (E6)\*

## Weight (Kg)

0.3

\* Colours on request

## Mounting

ceiling recessed

## Wiring

On the power supply unit with terminal board included. Available in DALI electronic versions.

## Notes

Central cover to complete the luminaire to be ordered with a separate item code - available in a standard finish, it is designed to be painted with a customised finish.

Complies with EN60598-1 and pertinent regulations



IP20


IP23



## Technical data

Im system:	1204	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
W system:	14.5	Voltage [Vin]:	230
Im source:	1450	Lamp code:	LED
W source:	12	Number of lamps for optical assembly:	1
Luminous efficiency (Im/W, real value):	83	ZVEI Code:	LED
Im in emergency mode:	-	Number of optical assemblies:	1
Total light flux at or above an angle of 90° [Lm]:	0	Power factor:	See installation instructions
Light Output Ratio (L.O.R.) [%]:	83	Inrush current:	5 A / 220 µs
Beam angle [°]:	40°	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 81 luminaires B16A: 130 luminaires C10A: 135 luminaires C16A: 221 luminaires
CRI (minimum):	80		
Colour temperature [K]:	4000	Minimum dimming %:	1
MacAdam Step:	2	Control:	DALI-2


## Polar



# Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	75	71	68	66	70	68	68	65	78
1.0	78	75	72	70	74	72	71	69	83
1.5	82	80	77	76	79	77	76	74	89
2.0	85	83	81	80	82	80	79	77	93
2.5	86	85	84	83	84	83	82	79	96
3.0	87	86	85	85	85	84	83	81	98
4.0	88	87	87	86	86	86	84	82	99
5.0	89	88	88	88	87	86	85	83	100

# Luminance curve limit



# UGR diagram

Corrected UGR values (at 1450 lm bare lamp luminous flux)											
Reflect.: ceiling/cav walls work pl. Room dim x y		viewed crosswise					viewed endwise				
2H	2H	4.3	4.8	4.5	5.1	5.3	4.4	5.0	4.7	5.2	5.4
	3H	4.1	4.6	4.4	4.9	5.2	4.3	4.8	4.6	5.0	5.3
	4H	4.1	4.5	4.4	4.8	5.1	4.2	4.7	4.5	5.0	5.3
	6H	4.0	4.4	4.3	4.7	5.1	4.1	4.5	4.5	4.9	5.2
	8H	3.9	4.4	4.3	4.7	5.0	4.1	4.5	4.4	4.8	5.2
	12H	3.9	4.3	4.3	4.6	5.0	4.0	4.4	4.4	4.8	5.1
4H	2H	4.1	4.5	4.4	4.8	5.1	4.2	4.7	4.5	5.0	5.3
	3H	3.9	4.3	4.3	4.6	5.0	4.0	4.4	4.4	4.8	5.1
	4H	3.8	4.2	4.2	4.5	4.9	3.9	4.3	4.3	4.7	5.1
	6H	3.7	4.0	4.2	4.4	4.9	3.9	4.2	4.3	4.6	5.0
	8H	3.7	4.0	4.1	4.4	4.8	3.8	4.1	4.3	4.5	5.0
	12H	3.6	3.9	4.1	4.3	4.8	3.8	4.0	4.2	4.5	4.9
8H	4H	3.7	4.0	4.1	4.4	4.8	3.8	4.1	4.3	4.5	5.0
	6H	3.6	3.8	4.1	4.3	4.7	3.7	4.0	4.2	4.4	4.9
	8H	3.5	3.7	4.0	4.2	4.7	3.7	3.9	4.2	4.3	4.8
	12H	3.5	3.7	4.0	4.1	4.7	3.6	3.8	4.1	4.3	4.8
12H	4H	3.6	3.9	4.1	4.3	4.8	3.8	4.0	4.2	4.5	4.9
	6H	3.5	3.7	4.0	4.2	4.7	3.7	3.9	4.2	4.3	4.8
	8H	3.5	3.7	4.0	4.1	4.7	3.6	3.8	4.1	4.3	4.8
Variations with the observer position at spacing:											
S =	1.0H	6.8 / -19.2					6.9 / -18.9				
	1.5H	9.6 / -20.8					9.7 / -20.2				
	2.0H	11.6 / -21.0					11.7 / -20.4				