



## Laser Blade XS

Design iGuzzini

iGuzzini

Last information update: October 2024



### Product code

QU99: Minimal 9 cells - Flood beam - LED

### Technical description

Square miniaturised recessed luminaire with 9 optical elements for LED lamps - fixed optic. Despite the ultracompact size of the product, the patented technology of the optic system guarantees an efficient luminous flux and a high level of controlled glare visual comfort. Main body with die-cast aluminium radiant surface, minimal (frameless) version for mounting flush with the ceiling. For recessed installation in a false ceiling a specific adapter is required that is available with a separate item code. Metallised, thermoplastic, high definition Opti Beam reflector, integrated in a set-back position in the anti-glare screen. Supplied with a dimmable DALI power supply unit connected to the luminaire.

### Installation

The luminaire is recessed in the specific adapter (QJ91) by means of a steel wire spring, previously installed on the ceiling that can be 12.5 / 15 / 20 mm thick. A special protective sheath allows finishing operations on the plasterboard to be simplified and speeded up.

### Colour

White (01) | Black (04) | Gold (14) | Burnished chrome (E6)

### Weight (Kg)

0.33

### Mounting

wall recessed|ceiling recessed

### Wiring

On the power supply unit with terminal board included.

### Notes

The special steel wire spring provided is required to facilitate the eventual extraction of the recessed body once it has been inserted.

Complies with EN60598-1 and pertinent regulations



### Technical data

lm system:	1214 (*)	Beam angle [°]:	42 (*)
W system:	18 (*)	CRI:	90
lm source:	1463 (*)	Colour temperature [K]:	3500
W source:	15 (*)	Number of lamps for optical assembly:	1
Luminous efficiency (lm/W, real value):	56 (*)	ZVEI Code:	LED
lm in emergency mode:	-	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	83 (*)	Control:	DALI-2