

Blade R downlight

Last information update: April 2025

Product configuration: QW39
QW39: accessory cover for diffused lighting - UGR < 19



Product code
QW39: accessory cover for diffused lighting - UGR < 19

Technical description
Round fixed luminaire designed to use LED lamps with C.o.B. technology. Version compatible with Blade R diam 170mm (18LED) complete with device for coupling it to the luminaire and DALI control gear with DT6 control System. Reflector vacuum-metallised with aluminium vapours with an anti-scratch protective layer. Dissipater made of painted grey die-cast aluminium. Product complete with LED lamp in warm white colour tone (3000K). Light emission UGR<19 L<3000 cd/m2 ideal for environments with video terminals.

Installation
Downlight accessory for Blade R diam 170mm (18LED)

Colour	Weight (Kg)
White / Aluminium (39) Black / Aluminium (40)	0.34

Complies with EN60598-1 and pertinent regulations



Technical data			
Im system:	722.5	CRI:	90
W system:	7.3	Colour temperature [K]:	3000
Im source:	850	MacAdam Step:	2
W source:	5.6	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25C)
Luminous efficiency (Im/W, real value):	98.97	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0.0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	85	Number of optical assemblies:	1
Beam angle [°]:	66°	Control:	DALI-2