


Last information update: May 2025

**Product configuration: R348**

R348: body Ø 117 mm - medium optic



**Product code**

R348: body Ø 117 mm - medium optic

**Technical description**

Adjustable mediumlight with adapter for installation on a mains voltage track. Luminaire made of die-cast aluminium. mediumlight double adjustability allows a 360° rotation about the vertical axis and 90° tilting relative to the horizontal plane. Built-in dimmable DALI ballast. Luminaire complete with C.O.B. technology LED unit in warm white colour 3000K. Anti-scratch reflector made of P.V.D (physical vapour deposition) aluminium that can provide optimum performance in terms of light efficiency. medium optic. Possibility of installing a flat accessory, like a glass cover or an elliptical distribution refractor. Interchangeable reflectors that can be ordered as an accessory.

**Installation**

On an electrified track or special base

**Colour**

White (01) | Black (04)

**Weight (Kg)**

1.1

**Mounting**

three circuit track

**Wiring**

Product complete with DALI components

Complies with EN60598-1 and pertinent regulations



IP20

IP40

With accessory installed



**Technical data**

lm system:	4505.0	CRI:	80
W system:	38.1	Colour temperature [K]:	3000
lm source:	5300	MacAdam Step:	2
W source:	34	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25C)
Luminous efficiency (lm/W, real value):	118.24	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0.0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	85	Number of optical assemblies:	1
Beam angle [°]:	22°	Control:	DALI-2