


Last information update: May 2025

**Product configuration: R362**

R362: body Ø 117 mm - food - flood optic



**Product code**

R362: body Ø 117 mm - food - flood optic

**Technical description**

Adjustable mediumlight with adapter for installation on a mains voltage track. Luminaire made of die-cast aluminium. mediumlight double adjustability allows a 360° rotation about the vertical axis and 90° tilting relative to the horizontal plane. Equipped with electronic ballast. Luminaire complete with C.O.B. technology LED unit with colour tone calibrated for fish products. Anti-scratch reflector made of P.V.D (physical vapour deposition) aluminium that can provide optimum performance in terms of light efficiency. Flood optic. Possibility of installing a flat accessory, like a glass cover or an elliptical distribution refractor. Interchangeable reflectors that can be ordered as an accessory.

**Installation**

On an electrified track or special base

**Colour**

White (01) | Black (04)

**Weight (Kg)**

1.1

**Mounting**

three circuit track

**Wiring**

Product complete with electronic components

Complies with EN60598-1 and pertinent regulations



**Technical data**

Im system:	3867.5	MacAdam Step:	3
W system:	37.9	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25C)
Im source:	4250	Lamp code:	LED
W source:	34	Number of lamps for optical assembly:	1
Luminous efficiency (Im/W, real value):	102.04	ZVEI Code:	LED
Im in emergency mode:	-	Number of optical assemblies:	1
Total light flux at or above an angle of 90° [Lm]:	0.0	Power factor:	See installation instructions
Light Output Ratio (L.O.R.) [%]:	91	Inrush current:	18 A / 250 µs
Beam angle [°]:	30°	Overvoltage protection:	0kV Common mode & 0kV Differential mode
CRI:	90	Control:	On/off
Colour temperature [K]:	6500		