


Last information update: November 2024

**Product configuration: R568.83+QX58.01**

R568.83: iN60 Space - LED module - L 2384 - UP (40%) DOWN (60%) emission - General Light - neutral - DALI - Transparent/Black  
QX58.01: iN60 MMO - Up and Down Module - Minimal - L= 2384 - 4000K - CRI 80 - White



**Product code**

R568.83: iN60 Space - LED module - L 2384 - UP (40%) DOWN (60%) emission - General Light - neutral - DALI - Transparent/Black

**Technical description**

LED module designed to be housed in iN60 system profiles - Up (40%) / Down (60%) light distribution - made up of an emission raster, lamp device and operating components. Version for general light emission. UP: translucent shaped PC diffuser screen. DOWN: high efficiency emission with a translucent textured thermoplastic raster, created with a catadioptric system (patented Opti Beam Diamond optic) - with no galvanic treatments - combined with a PP cover with a gloss finish and an additional diffuser screen. The resulting optic system generates an extremely elegant and professional light emission. Integrated DALI dimmable driver.

**Installation**

Module insertion on compartments with a mechanical easy-push system (steel snap-on springs).

**Colour**

Black Transparent (83)

**Weight (Kg)**

1.9

**Wiring**

Quick coupling input terminal block connection. LED module complete with integrated DALI control gear. The electrical cables used are made of a "halogen free" material.

Complies with EN60598-1 and pertinent regulations



**Product code**

QX58.01: iN60 MMO - Up and Down Module - Minimal - L= 2384 - 4000K - CRI 80 - White

**Technical description**

The L profile=2384 mm is made of extruded aluminium. This is the Minimal version for up (4000K and CRI80) and down emission. The product can be used for pendant applications; in both a stand alone version and when the product is used in continuous lines.

**Installation**

Installation can be pendant-mounted using suitable accessories to be ordered separately. The modules are completed with end caps and rasters with LEDs to be ordered separately.

**Colour**

White (01)


**Weight (Kg)**

4

**Mounting**

ceiling recessed|wall surface|ceiling pendant

Complies with EN60598-1 and pertinent regulations



#### Technical data

Im system:	12636	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W system:	91	Lamp code:	LED
Im source:	17550	Number of lamps for optical assembly:	1
W source:	82	ZVEI Code:	LED
Luminous efficiency (Im/W, real value):	138.9	Number of optical assemblies:	1
Im in emergency mode:	-	Power factor:	See installation instructions
Total light flux at or above an angle of 90° [Lm]:	4457	Inrush current:	53 A / 200 µs
Light Output Ratio (L.O.R.) [%]:	72	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 8 luminaires B16A: 13 luminaires C10A: 13 luminaires C16A: 22 luminaires
CRI (minimum):	80	Minimum dimming %:	1
Colour temperature [K]:	4000	Overvoltage protection:	2kV Common mode & 1kV Differential mode
MacAdam Step:	3	Control:	DALI-2

#### Polar

