

Palco Low Voltage

Design Artec
Studio


iGuzzini

Last information update: May 2025

Product configuration: RC49.01+MY23.65

RC49.01: Palco LV spotlight Ø 62 - Spot beam - Bluetooth - 18.3W 1232lm - 3000K - CRI 90 - White

MY23.65: "Soft Lens" filter - Nitric



Product code

RC49.01: Palco LV spotlight Ø 62 - Spot beam - Bluetooth - 18.3W 1232lm - 3000K - CRI 90 - White **Attention! Code no longer in production**

Technical description

Adjustable spotlight with adapter for installation on 48V low voltage track. Made of die-cast aluminium with passive dissipation system. The adapter made of a thermoplastic material includes the DC/DC driver circuit and Bluetooth protocol. The swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic unit guarantees a high level of visual comfort. OPTI BEAM LENS lighting system with hi-tech optic lens that creates a particularly well-defined light beam. A rapid tool-free system for connecting the adapter electrically and mechanically to the track. The 48V track coupling device is fitted with a mechanical anti-fall safety double block. Luminaire with Bluetooth Low Energy technology (WiSilica). Frequency 2.4 GHz BLE. The luminaire can be controlled with the Quick BLE system and Smart Light Control app that enable on-off, dimming and scene recall functions. The app is available on the Apple Store and Google Play Store. It can be integrated in the system's "Mesh" network that allows multiple luminaires to be controlled. OTA (over the air) update via app. Integrated Beacon that can be activated via Smart Light Control (Eddystone, iBeacon, Alt Beacon) that enables functions including push notification and indoor navigation-wayfinding.

Installation

An adapter is used to fix the device mechanically and tool-free to the 48V track. Max luminaire-luminaire distance (*): 8 m; max smartphone-luminaire distance (*): 20 m.

Colour
White (01)

Weight (Kg)
0.41

Mounting

Low voltage track

Wiring

Direct connection on 48V track. Track power supply unit to be ordered separately. Luminaire can be controlled with Bluetooth technology (WiSilica)

Notes

(*) The maximum distance for Bluetooth installations is affected by physical obstacles, like walls, metal panels and the layout of the system. We suggest that a test is conducted at the installation site. Technical and anti-glare accessories available; with option of the combined installation of two internal accessories.

Complies with EN60598-1 and pertinent regulations



Accessory code

MY23.65: "Soft Lens" filter - Nitric

Technical description

Prismatic glass accessory that softens and diffuses the light beam.

Installation

Surface-mounted: remove the recessed luminaire safety glass and replace it with the accessory screen.

Colour
Nitric (65)

Weight (Kg)
0.02

Complies with EN60598-1 and pertinent regulations

Technical data

Im system:	1120	MacAdam Step:	2
W system:	18.3	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Im source:	1600	Voltage [Vin]:	48
W source:	17	Lamp code:	LED
Luminous efficiency (Im/W, real value):	61.2	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	70	LED current [mA]:	450
Beam angle [°]:	18° / 16°	Power factor:	See installation instructions
CRI (minimum):	90	Minimum dimming %:	1
Colour temperature [K]:	3000	Control:	Bluetooth WiSilica

Polar

