



Light Shed dB 60

Last information update: April 2025



Product code

RC89: 596X596 - Sound-absorbent - No Light Emission - designed for smart accessory installation

Technical description

596x596 mm luminaire for pendant installation or surface-mounted on a modular grille, with no light emission. Body made of thermal insulating, sound-absorbent, 85% recycled polyester fibre material. OEKO-TEX certified, standard 100, class I, hypoallergenic, skin contact safe product. Waterproof, breathable, non putrescible panel. Versions with option of integrating smart accessories, like a BLE multi-sensor, DALI 2 sensor, speaker, camera and an environment sensor to be ordered separately. Recessed in plasterboard ceilings using a frame to be ordered as an accessory. The product can be pendant-mounted using accessories to be ordered separately.

Installation

Surface-mounted on 600x600 mm modular panels. Recessed in plasterboard false ceilings using a frame accessory to be ordered separately. Pendant-mounted using accessories to be ordered separately.

Colour

White (01) | Grey (15) | Blue (16) | Light green (81)




Weight (Kg)

1.2



Notes

See graph for acoustic calculation in Documentation Other colours and customised features are available on request.
TPb rated

Complies with EN60598-1 and pertinent regulations



On the visible part of the product once installed



Technical data

lm system:	-	Luminous efficiency (lm/W, 0 real value):
W system:	-	
lm source:	-	lm in emergency mode: -
W source:	-	Number of optical assemblies: 0