


Last information update: October 2024

Product configuration: RG93.I8+MD02

RG93.I8: Zurigo - Pendant Ø820 - clear transparent / coloured screen - Matte blue

**Product code**

RG93.I8: Zurigo - Pendant Ø820 - clear transparent / coloured screen - Matte blue

Technical description

Direct light pendant luminaire. E27 3000K LED lamp (not included). Thermoplastic power supply base for securing to installation surface with terminal board for electrical connections, safety cable clamp for power supply cable and steel pendant cable piston adjustment and securing system. The cables supplied are a standard length of 2000 mm. Eventual adjustments and excess cable can be regulated on the base during installation. White plastic base cover - bayonet coupling system. Transparent or coloured methacrylate screen (coloured version with white interior). Recommended lamp available with separate item code.

Installation

Power supply base fixed to ceiling with screws and screw anchors (included).

Colour

Matte blue (I8)

Weight (Kg)

4.3

Mounting

ceiling pendant

Wiring

Terminal board on power supply base for mains cable connections and safety cable clamp for power supply cable - steel pendant cable millimetric adjustment piston system.

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	1412	CRI (minimum):	80
W system:	18	Colour temperature [K]:	3000
lm source:	-	MacAdam Step:	6
W source:	-	Lamp code:	LED
Luminous efficiency (lm/W, real value):	78.4	Socket:	E27
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	76	Number of optical assemblies:	1

Polar