

Libera Stand-alone


Design Artec
Studio

iGuzzini

Last information update: April 2025

Product configuration: RS47.M6

RS47.M6: Luminaire with Up/Down emission L=1428 - General Light - High Output - Space Frameless optic -- 29.9W 3869.3lm - 3500K - CRI 90 - White/Black Transparent



Product code

RS47.M6: Luminaire with Up/Down emission L=1428 - General Light - High Output - Space Frameless optic -- 29.9W 3869.3lm - 3500K - CRI 90 - White/Black Transparent

Technical description

Direct (70%) / Indirect (30%) emission luminaire with 3500K CRI90 monochrome LED lamps. Opti-Diamond (High Output) Down General Light Space optic available in a White Cover (Transparent white) or Black Cover (Transparent black) version. Up General Light optic with opal screen. Frameless version extruded aluminium profile with die-cast zamak end caps. Complete with power and pendant cable L=3000. Steel pendant mount cable with millimetric adjustment system and brass component. Ceiling-mounted base in painted aluminium with galvanised steel wall plate. Product supplied with DALI dimmable electronic power supply unit positioned inside the aluminium base.

Installation

Pendant-mounted. Complete with power and pendant cables L=3000 with brass ceiling-fixing component

Colour

White/Black Transparent (M6)

Weight (Kg)

1.55

Mounting

ceiling pendant


Wiring

Product complete with DALI power supply unit positioned inside the base.

Complies with EN60598-1 and pertinent regulations



IP20



Technical data

lm system: 3518
W system: 27
lm source: 4690
W source: 27
Luminous efficiency (lm/W, 130.3
real value):
lm in emergency mode: -
Total light flux at or above 1293
an angle of 90° [Lm]:
Light Output Ratio (L.O.R.) 75
[%]:

CRI (minimum): 90
Colour temperature [K]: 3500
MacAdam Step: 3
Lamp code: LED
Number of lamps for optical 1
assembly:
ZVEI Code: LED
Number of optical 1
assemblies:
Control: DALI-2

Polar

