

Last information update: February 2025

**Product configuration: RU06.01+RV33.01+RU58.38**

RU06.01: Linear module - recessed Minimal Down - for Opal or MPO screen - L=597 - White

RV33.01: Plate with Warm White LED - Downlight UGR<19 - DALI - L=598 - 4.7W 480lm - 3000K - White

RU58.38: Single Microprismatic screen L=1200 (UGR) - Opaline


**Product code**

RU06.01: Linear module - recessed Minimal Down - for Opal or MPO screen - L=597 - White

**Technical description**

Recessed Minimal (Frameless) version with extruded aluminium profile installed flush with ceiling. Designed for use with an Opal or Microprismatic (MPO) single or roll screen (for continuous line versions).

**Installation**

Can be recess-mounted.

**Colour**

Aluminium (12)

**Wiring**

Designed to house the LED modules that can be used by system.

Complies with EN60598-1 and pertinent regulations


**Product code**

RV33.01: Plate with Warm White LED - Downlight UGR<19 - DALI - L=598 - 4.7W 480lm - 3000K - White

**Technical description**

Warm White LED plate with direct (Down) light emission. Version with UGR<19 controlled luminance ( $L \leq 3000 \text{cd/m}^2$ ) ideal for environments with video monitors. To be combined with a Microprismatic screen (single or roll) to be ordered separately. The module optic and structural fittings allow high system efficiency values to be achieved. DALI dimmable power supply integrated in the luminaire. Extruded aluminium heat sink and "Halogen Free" electric cables.

**Installation**

Module insertion on profiles facilitated by a quick coupling system.

**Colour**

White (01)

**Wiring**

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable DALI power supply.

Complies with EN60598-1 and pertinent regulations




IP20



pending

pending


**Accessory code**

RU58.38: Single Microprismatic screen L=1200 (UGR) - Opaline

**Technical description**

Flexible single Microprismatic screen for composition L=1200 - UGR< 19 optic -

**Installation**

snapped on via special springs located in the profile

**Colour**

Opaline (38)

**Notes**

TPa rated

Complies with EN60598-1 and pertinent regulations

---

**Technical data**

Im system:	480	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W system:	4.7	Lamp code:	LED
Im source:	750	Number of lamps for optical assembly:	1
W source:	3.5	ZVEI Code:	LED
Luminous efficiency (Im/W, real value):	102.1	Number of optical assemblies:	1
Total light flux at or above an angle of 90° [Lm]:	0	Power factor:	See installation instructions
Light Output Ratio (L.O.R.) [%]:	64	Minimum dimming %:	1
CRI (minimum):	80	Overvoltage protection:	2kV Common mode & 1kV Differential mode
Colour temperature [K]:	3000	Control:	DALI-2
MacAdam Step:	3		

---

**Polar**