

Last information update: March 2025

### Product configuration: RU32.12+RV69.12

RU32.12: Linear module - recessed Minimal Down - for MMO/Space/Wall Washer versions - L=1192 - Aluminium

RV69.12: Plate with LED - MMO Downlight - UGR<19 - HO - DALI - L=1192 - 27.7W 3834.6lm - 3500K - Aluminium



### Product code

RU32.12: Linear module - recessed Minimal Down - for MMO/Space/Wall Washer versions - L=1192 - Aluminium

### Technical description

Recessed Minimal (Frameless) version with extruded aluminium profile installed flush with ceiling. Designed for use with an LED plate in MMO, Space and Wall Washer versions.

### Installation

Can be recess-mounted.

### Colour

Aluminium (12)

### Wiring

Designed to house the LED modules that can be used by the system.

Complies with EN60598-1 and pertinent regulations



### Product code

RV69.12: Plate with LED - MMO Downlight - UGR<19 - HO - DALI - L=1192 - 27.7W 3834.6lm - 3500K - Aluminium

### Technical description

3500K LED plate with direct (Down) light emission in MMO version. High Output (HO) version with controlled luminance down emission  $L \leq 3000 \text{ cd/m}^2 - \alpha > 65^\circ$ , for use in environments with video monitors in compliance with EN 12464-1. The module optic and structural fittings allow high luminous flux and system efficiency values. DALI dimmable power supply integrated in the luminaire. Extruded aluminium heat sink and "Halogen Free" electric cables. Moulded and metallised polycarbonate raster.

### Installation

Module insertion on profiles facilitated by a quick coupling system.

### Colour

Aluminium (12)

### Wiring

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable DALI power supply.

### Notes

TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations




IP20



### Technical data

Im system:	3835	Colour temperature [K]:	3500
W system:	27.7	MacAdam Step:	3
Im source:	4980	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W source:	24	Lamp code:	LED
Luminous efficiency (Im/W, real value):	138.4	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	77	Number of optical assemblies:	1
CRI (minimum):	80	Control:	DALI-2


# Polar



# Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	65	60	56	54	59	56	56	53	68
1.0	69	64	61	59	63	61	60	57	74
1.5	74	70	68	66	69	67	67	64	83
2.0	77	74	72	71	73	71	71	68	88
2.5	78	76	75	74	75	74	73	71	92
3.0	79	78	77	76	77	76	75	72	94
4.0	81	79	78	78	78	77	76	74	96
5.0	81	80	79	79	79	78	77	75	97

# Luminance curve limit



# UGR diagram

Corrected UGR values (at 4980 lm bare lamp luminous flux)												
Reflect.: ceiling/cav walls work pl. Room dim x y		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30	0.30
		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30	0.30
		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
		viewed crosswise					viewed endwise					
2H	2H	17.6	18.2	17.8	18.4	18.7	17.4	18.0	17.7	18.3	18.5	18.5
	3H	17.4	18.0	17.7	18.3	18.5	17.3	17.9	17.6	18.1	18.4	18.4
	4H	17.3	17.9	17.7	18.2	18.5	17.2	17.8	17.6	18.1	18.4	18.4
	6H	17.3	17.8	17.6	18.1	18.4	17.1	17.6	17.5	18.0	18.3	18.3
	8H	17.2	17.7	17.6	18.0	18.4	17.1	17.6	17.5	17.9	18.2	18.2
	12H	17.2	17.6	17.6	18.0	18.3	17.1	17.5	17.4	17.9	18.2	18.2
4H	2H	17.4	17.9	17.7	18.2	18.5	17.2	17.7	17.5	18.0	18.3	18.3
	3H	17.2	17.7	17.6	18.0	18.4	17.1	17.5	17.4	17.9	18.2	18.2
	4H	17.1	17.5	17.5	17.9	18.3	17.0	17.4	17.4	17.7	18.1	18.1
	6H	17.0	17.4	17.5	17.8	18.2	16.9	17.2	17.3	17.6	18.1	18.1
	8H	17.0	17.3	17.4	17.7	18.2	16.9	17.2	17.3	17.6	18.0	18.0
	12H	17.0	17.2	17.4	17.7	18.1	16.8	17.1	17.3	17.5	18.0	18.0
8H	4H	17.0	17.3	17.4	17.7	18.2	16.9	17.2	17.3	17.6	18.0	18.0
	6H	16.9	17.2	17.4	17.6	18.1	16.8	17.0	17.2	17.5	17.9	17.9
	8H	16.9	17.1	17.3	17.5	18.0	16.7	16.9	17.2	17.4	17.9	17.9
	12H	16.8	17.0	17.3	17.5	18.0	16.7	16.9	17.2	17.3	17.9	17.9
12H	4H	17.0	17.2	17.4	17.7	18.1	16.8	17.1	17.3	17.5	18.0	18.0
	6H	16.9	17.1	17.3	17.5	18.0	16.7	16.9	17.2	17.4	17.9	17.9
	8H	16.8	17.0	17.3	17.5	18.0	16.7	16.9	17.2	17.3	17.9	17.9
Variations with the observer position at spacing:												
S =		1.0H	3.6 / -10.1				3.6 / -8.7					
		1.5H	5.2 / -22.0				5.1 / -18.4					
		2.0H	7.2 / -22.4				7.1 / -18.5					