

iN60 Evo Stand-alone

Design iGuzzini

iGuzzini

Last information update: May 2025

Product configuration: RZ00.L2

RZ00.L2: Pendant-mounted Stand Alone LED - Up/Down - DALI - GL - LO - Opal - L=1200 - 27W 3427.2lm - 3500K - White / Opal White

Product code

RZ00.L2: Pendant-mounted Stand Alone LED - Up/Down - DALI - GL - LO - Opal - L=1200 - 27W 3427.2lm - 3500K - White / Opal White

Technical description

Stand Alone pendant-mounted luminaire. The product consists of an extruded aluminium profile with zamak end caps. 3500K LED plate with direct (Down) and indirect (Up) light emission. Low Output (LO) version for General Light profiles. The module optic and structural fittings allow high luminous flux and system efficiency values. DALI dimmable power supply integrated in the luminaire. Extruded aluminium heat sink and "Halogen Free" electric cables. For indirect light (Up), we supply an extruded aluminium support plate that is painted white to increase reflection. Opal PMMA diffuser screen. Pendant and power supply cables L=1500


Installation

Pendant-mounted

Colour

White / Opal White (L2)

Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	3427	Colour temperature [K]:	3500
W system:	27	MacAdam Step:	3
Im source:	5040	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W source:	24	Lamp code:	LED
Luminous efficiency (Im/W, real value):	126.9	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	1479	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	68	Control:	DALI-2
CRI (minimum):	80		

Polar

