

iN60 Evo Stand-alone

Design iGuzzini

iGuzzini

Last information update: February 2025

Product configuration: RZ25.12

RZ25.12: Pendant-mounted Stand Alone - Neutral White LED - Up/Down - DALI - GL - HO - MMO - L=1200 - 46.3W 6832.8lm - 4000K - Aluminium



Product code

RZ25.12: Pendant-mounted Stand Alone - Neutral White LED - Up/Down - DALI - GL - HO - MMO - L=1200 - 46.3W 6832.8lm - 4000K - Aluminium

Technical description

Stand Alone pendant-mounted luminaire. The product consists of an extruded aluminium profile with zamak end caps. Neutral White LED plate with direct (Down) and indirect (Up) light emission. High Output (HO) version for General Light profiles. The module optic and structural fittings allow high luminous flux and system efficiency values. DALI dimmable power supply integrated in the luminaire. Extruded aluminium heat sink and "Halogen Free" electric cables. For indirect light (Up), we supply an extruded aluminium support plate that is painted white to increase reflection. Metallised polycarbonate raster. Pendant and power supply cables L=1500


Installation

Pendant-mounted

Colour

Aluminium (12)

Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	6833	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W system:	46.3	Lamp code:	LED
Im source:	8760	Number of lamps for optical assembly:	1
W source:	41	ZVEI Code:	LED
Luminous efficiency (Im/W, real value):	147.6	Number of optical assemblies:	1
Im in emergency mode:	-	Power factor:	See installation instructions
Total light flux at or above an angle of 90° [Lm]:	2422	Inrush current:	53 A / 200 µs
Light Output Ratio (L.O.R.) [%]:	78	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 8 luminaires B16A: 13 luminaires C10A: 13 luminaires C16A: 22 luminaires
CRI (minimum):	80	Minimum dimming %:	1
Colour temperature [K]:	4000	Overvoltage protection:	2kV Common mode & 1kV Differential mode
MacAdam Step:	3	Control:	DALI-2

Polar

