

Last information update: February 2025

Product configuration: RZ32.12

RZ32.12: Pendant-mounted Stand Alone - Warm White LED - Up/Down - DALI - GL - HO - MMO - L=2400 - 92.6W 10865.4lm - 3000K - CRI 90 - Aluminium

**Product code**

RZ32.12: Pendant-mounted Stand Alone - Warm White LED - Up/Down - DALI - GL - HO - MMO - L=2400 - 92.6W 10865.4lm - 3000K - CRI 90 - Aluminium

Technical description


Stand Alone pendant-mounted luminaire. The product consists of an extruded aluminium profile with zamak end caps. Warm White LED plate with direct (Down) and indirect (Up) light emission. High Output (HO) version for General Light profiles. The module optic and structural fittings allow high luminous flux and system efficiency values. DALI dimmable power supply integrated in the luminaire. Extruded aluminium heat sink and "Halogen Free" electric cables. For indirect light (Up), we supply an extruded aluminium support plate that is painted white to increase reflection. Metallised polycarbonate raster. Pendant and power supply cables L=1500

Installation

Pendant-mounted

Colour

Aluminium (12)



Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	10865	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W system:	92.6	Lamp code:	LED
lm source:	13930	Number of lamps for optical assembly:	1
W source:	82	ZVEI Code:	LED
Luminous efficiency (lm/W, real value):	117.3	Number of optical assemblies:	1
lm in emergency mode:	-	Power factor:	See installation instructions
Total light flux at or above an angle of 90° [Lm]:	3851	Inrush current:	53 A / 200 µs
Light Output Ratio (L.O.R.) [%]:	78	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 8 luminaires B16A: 13 luminaires C10A: 13 luminaires C16A: 22 luminaires
CRI (minimum):	90	Minimum dimming %:	1
Colour temperature [K]:	3000	Overvoltage protection:	2kV Common mode & 1kV Differential mode
MacAdam Step:	3	Control:	DALI-2

Polar