


Last information update: February 2025

Product configuration: RZ63.M6

RZ63.M6: Pendant-mounted Stand Alone LED - Up/Down - DALI - UGR<19 - LO - SPACE - L=1200 - 19W 2539.2lm - 3500K - CRI 90 - White/Black Transparent

**Product code**

RZ63.M6: Pendant-mounted Stand Alone LED - Up/Down - DALI - UGR<19 - LO - SPACE - L=1200 - 19W 2539.2lm - 3500K - CRI 90 - White/Black Transparent

Technical description

Stand Alone pendant-mounted luminaire. The product consists of an extruded aluminium profile with zamak end caps. 3500K LED plate with direct (Down) and indirect (Up) light emission. Low Output (LO) version with controlled luminance emission ($L \leq 3000 \text{ cd/m}^2$) ideal for environments with video monitors ($\text{UGR} < 19$). Opti-Diamond Space optic available in a White Cover (Transparent white) or Black Cover (Transparent black) version. The module optic and structural fittings allow high luminous flux and system efficiency values. DALI dimmable power supply integrated in the luminaire. Extruded aluminium heat sink and "Halogen Free" electric cables. For indirect light (Up), we supply an extruded aluminium support plate that is painted white to increase reflection. Transparent PMMA raster with rear cover available in black or white PP according to the version. Pendant and power supply cables L=1500


Installation

Pendant-mounted

Colour

White/Black Transparent (M6)

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	3830	CRI (minimum):	90
W system:	30	Colour temperature [K]:	3500
lm source:	5320	MacAdam Step:	3
W source:	30	Lamp code:	LED
Luminous efficiency (lm/W, real value):	127.7	Number of lamps for optical assembly:	1
lm in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	1351	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	72	Control:	DALI-2

Polar