


Last information update: July 2024

**Product configuration: S835+GOBO40A**

S835: Framer with flange - Warm White - Integrated power supply - DALI - Framer - Class II

GOBO40A: Gobo ø40mm - max focusing

**Product code**

S835: Framer with flange - Warm White - Integrated power supply - DALI - Framer - Class II

**Technical description**

Floodlight with LED lamp and framer. Consisting of an optical assembly made of EN1706AC 46100LF aluminium alloy and a forged steel flange for installation on cylindrical-conical poles. The optical assembly is subjected to a multi-step, pre-treatment process in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The following painting stage consists of a primer and a liquid acrylic paint, cured at 150°C, with a high level of weather and UV ray resistance. The optical assembly is fitted with a 5 mm thick tempered sodium-calcium glass cover. The product can be positioned at 340° on the vertical plane and 90° on the horizontal plane. The product is fitted with a 7m cable hidden inside the flange and can be installed on cylindrical-conical poles using the slots in the flange. A monochrome LED circuit is located inside the product with an Opti Beam optic system. The product is supplied with two Ø40mm and Ø30mm gobos that allow 26° and 18° light cones and blades for defining geometrical patterns. Both the gobos and blades can be installed magnetically inside the product. Dichroic glass gobos (to be purchased separately) can be used by fitting the adjustable gobo holder (code X457 to be purchased separately) or sheet metal gobos that are installed magnetically. The power supply unit and DALI protocol are included in the product code. All external screws are made of A2 stainless steel.

**Installation**

Pole installations can be made using two M10 screws included in the end product code.

**Colour**

White (01) | Black (04) | Grey (15) | Rust Brown (F5)

**Weight (Kg)**

6.41

**Mounting**

pole-top side entry

**Notes**

Insulation class II These products can be used at a maximum ambient temperature of 50°C.

Complies with EN60598-1 and pertinent regulations

**Technical data**

Im system:	1349	Life Time LED 2:	100,000h - L90 - B10 (Ta 40°C)
W system:	27.8	Lamp code:	LED
Im source:	3550	Number of lamps for optical assembly:	1
W source:	24	ZVEI Code:	LED
Luminous efficiency (Im/W, real value):	48.5	Number of optical assemblies:	1
Im in emergency mode:	-	Intervallo temperatura ambiente:	from -30°C to 50°C.
Total light flux at or above an angle of 90° [Lm]:	0	Power factor:	See installation instructions
Light Output Ratio (L.O.R.) [%]:	38	Inrush current:	20 A / 50 µs
CRI (minimum):	80	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 34 luminaires B16A: 55 luminaires C10A: 57 luminaires C16A: 93 luminaires
Colour temperature [K]:	3000	Minimum dimming %:	1
MacAdam Step:	2	Overvoltage protection:	2kV Common mode & 2kV Differential mode
Life Time LED 1:	100,000h - L90 - B10 (Ta 25°C)	Control:	DALI-2

Polar

