

Libera Stand-alone



Design Artec
Studio

iGuzzini

Last information update: May 2025

Product configuration: SJ93(BR)

SJ93: Linear pendant Up/Down luminaire L=1828 - Space Frame optic - UGR<19 -



Product code

SJ93: Linear pendant Up/Down luminaire L=1828 - Space Frame optic - UGR<19 -

Technical description

Direct (70%) / Indirect (30%) emission luminaire with 3000K CRI90 monochrome LED lamps. Version for UGR < 19 controlled luminance emission - in compliance with the standard for use in environments with video monitors. Opti-Diamond Space optic available with a White (transparent white) or Black Cover (transparent black). Frame version extruded aluminium profile with die-cast zamak end caps. Complete with power and pendant cable L=3000 that can be adjusted as required. Steel pendant mount cable with millimetric adjustment system and brass component. Complete with 48Vdc Mid-Power Led circuit and DALI dimming system. "Powerline" technology allows each product connected to the system to be adjusted separately.

Installation

A tool-free system for connecting the product electrically and mechanically to the 48V Filorail low voltage track.

Colour

White/White Transparent (G0) | Black/Black Transparent (G1) | Black/White Transparent (G2) | White/Black Transparent (M6) | Titanium/White Transparent (P9) | Titanium/Black Transparent (Q0) | Sapphire blue/White Transparent (Q1) | Sapphire blue/Black Transparent (Q2)

Weight (Kg)

1.37

Mounting

ceiling pendant

Wiring

Power supply unit (48V) to be ordered separately as specified in the instruction sheet.

Complies with EN60598-1 and pertinent regulations



IP20



Technical data

Im system:	2491.5	MacAdam Step:	3
W system:	19.8	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25C)
Im source:	3300	Voltage [Vin]:	48
W source:	19	Lamp code:	LED
Luminous efficiency (Im/W, real value):	125.83	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	967.7	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	76	Power factor:	See installation instructions
Beam angle [°]:	61°	Overvoltage protection:	0kV Common mode & 0kV Differential mode
CRI:	90	Control:	DALI
Colour temperature [K]:	3000		