


Last information update: March 2025

Product configuration: SR28.15SR28.15: 47 surface Integral – Neutral White – 220÷240Vac DMX512-RDM – L=340mm – Wall Grazing Medium optic - 14.9W
756lm - 4000K - Grey**Product code**SR28.15: 47 surface Integral – Neutral White – 220÷240Vac DMX512-RDM – L=340mm – Wall Grazing Medium optic - 14.9W
756lm - 4000K - Grey**Technical description**

Direct light luminaire, designed to use monochrome LED lamps, DMX512-RDM 220÷ 240Vac dimmable with searching and addressing function. Ceiling, wall or surface-mounted. It consists of a body and installation brackets to be ordered separately. The body is made of extruded aluminium and includes die-cast aluminium end caps with 50/60 Shore A silicone seals. It is subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The following painting stage consists of a primer and a liquid acrylic paint, cured at 150°C, with a high level of weather and UV ray resistance. The top of the optical assembly is closed by a 3 mm thick transparent glass screen, fixed with silicone. Complete with multi-LED plate in Neutral White and a DMX512-RDM 220÷240Vac DALI electronic driver (power supply included). Supplied with a double PG11 and outlet cables for pass-through wiring with IP68 male/female joiners. Fitted with optics with a plastic (methacrylate) lens for Wall Grazing Medium lighting. All external screws used are made of A2 stainless steel. The luminaire technical characteristics conform to EN 60598-1 standards and particular requirements.

Colour

Grey (15)

Mounting

wall arm|wall surface|ceiling surface

Wiring

Complete with DMX-RDM control card and a 220-240V ac electronic power supply. The product is supplied with a nickel-plated brass PG11 double cable gland with H07RN-F 5x1, 5mm² rubber outlet cables for pass-through wiring with male and female IP68 connectors. Available for electrical connection and DMX-RDM control: IP68 5-pin female connector, IP68 5-pin male connector + closing cap (BZI6), and IP68 5-pin male + female connectors.

Notes


Product complete with LED lamp. DMX specifications require the insertion of a 120 Ohm terminating resistor to be placed between the DATA+ and DATA- cables of the last product in the line (BZQ7).

Complies with EN60598-1 and pertinent regulations

**Technical data**

Im system:	756	MacAdam Step:	3
W system:	14.9	Life Time LED 1:	100,000h - L80 - B10 (Ta 25°C)
Im source:	1400	Life Time LED 2:	100,000h - L80 - B10 (Ta 40°C)
W source:	10	Voltage [Vin]:	230
Luminous efficiency (Im/W, real value):	50.7	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	54	Number of optical assemblies:	1
CRI (minimum):	80	Intervallo temperatura ambiente:	from -30°C to 50°C.
Colour temperature [K]:	4000	Control:	DMX-RDM

Polar



Illuminances

Lux													Wall distance = 1m
3	0.1	0.3	0.6	2	4	5	4	2	0.6	0.3	0.1		
2	0.8	2	3	5	9	11	9	5	3	2	0.8		
	1	2	4	9	17	21	17	9	4	2	1		
1	1	2	5	11	18	24	18	11	5	2	1		
	2	3	6	10	16	21	16	10	6	3	2		
0	m	-2	-1	0	1	2	3						