

Last information update: May 2025

**Product configuration: UG32**

UG32: 27 Surface Full Remote - RGBW (W=3000K) - 48 Vdc - L=920mm - General Light No Dot optic

**Product code**

UG32: 27 Surface Full Remote - RGBW (W=3000K) - 48 Vdc - L=920mm - General Light No Dot optic

**Technical description**

Direct light linear luminaire, designed to use LED RGBW (W=3000K) lamps. The product can be installed using pairs of arms, ceiling/ground/wall-mounting bases, stakes, and pendant rods and cables (to be ordered separately). The body is made of extruded aluminium and includes die-cast aluminium end caps with 50/60 Shore A silicone seals. It is subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The following painting stage consists of a primer and a liquid acrylic paint, cured at 150°C, with a high level of weather and UV ray resistance. The top of the optical assembly is closed by a 5mm thick transparent glass screen, fixed with silicone. Complete with RGBW (W=3000K) multi-LED circuit. The product is fitted with a black-painted, copper alloy microlouvre to increase visual comfort while maintaining uniformity. Both the 48Vdc control card (available in a DMX version and a DALI version) and the power supply must be purchased separately. Supplied with a connector with an IP68 threaded locknut. The products have a double connector (male/female) to allow pass-through wiring and continuous line applications. The product is supplied with a closure cover (UV-resistant) that covers the cables and protects against dirt and UV rays. Fitted with a No Dot optical system. All external screws used are made of A2 stainless steel.

**Installation**

Installation accessories can be purchased separately, including arms for wall installations at a height of less than 3m, arms for wall installations at a height of more than 3m, bases for ceiling or wall-mounted installations, stakes, and pendant rods and cables.

**Colour**

White (01) | Black (04) | Grey (15) | Rust Brown (F5)

**Weight (Kg)**

1.12

**Mounting**

wall arm|wall surface|ceiling surface

**Wiring**

Ceiling, wall, surface, stake and pendant installation.

**Notes**

Supplied with a connector with an IP68 threaded locknut. The products have a double connector (male/female) to allow pass-through wiring and continuous line applications. Both the control card and power supply are remote and must be purchased separately. Life Time only LED White on: 100,000h - L85 - B10 (Ta 25°C) Life Time only LED White on: 100,000h - L85 - B10 (Ta 40°C) Life Time only RGB on: 31,000h - L70 - B50 (Ta 25°C) Life Time n.1 Color LED on: 45,000h - L70 - B50 (Ta 25°C)

Complies with EN60598-1 and pertinent regulations



IK06

IP66

**Technical data**

Im system:	337	Voltage [Vin]:	48
W system:	16.3	Lamp code:	LED
Im source:	935	Number of lamps for optical assembly:	1
W source:	8.5	ZVEI Code:	LED
Luminous efficiency (Im/W, real value):	20.7	Number of optical assemblies:	1
Im in emergency mode:	-	Intervallo temperatura ambiente:	from -30°C to 35°C.
Total light flux at or above an angle of 90° [Lm]:	0	LED current [mA]:	10
Light Output Ratio (L.O.R.) [%]:	36	Control:	PWM
Colour temperature [K]:	RGBW - 3000K		

Polar

