

Constant current power supply unit DALI/Step-Dim/Middle of the night profile IP20 40W - VIN = 220-240 VAC 50/60Hz - Iout =350mA

Design iGuzzini

iGuzzini

Last information update: January 2025



Accessory code

X210: Constant current power supply unit DALI/Step-Dim/Middle of the night profile IP20 40W - VIN = 220-240 VAC 50/60Hz - Iout =350mA

Technical description

DALI 40W dimmable electronic ballast, with STEP-DIM, ASTRO-DIM and MIDNIGHT PROFILE functions, Vout=18÷56Vdc, Iout=350mA (SELV) IP20 protection rating.

Colour
Indeterminate (00)

Weight (Kg)
0.26

Dimension (mm) (*)
123x79x33

* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.

Wiring

Make the connections on the appropriate terminal blocks

Notes

Overvoltage protection: 10kV Common Mode, 6kV Differential Mode

Complies with EN60598-1 and pertinent regulations



IP20



Technical data

Frequency [Hz]: 50/60

Current out [mA]: 350

Inrush current: 31 A / 186 μ s

Maximum number of LED power supply units of this type per miniature circuit breaker:

B10A: 18 power supply units
B16A: 30 power supply units
C10A: 31 power supply units
C16A: 51 power supply units

Minimum dimming %:

10

Overvoltage protection:

10kV Common mode & 6kV Differential mode