

**Constant current power supply unit DALI with outgoing cables IP68 25W - VIN =110-240VAC 50/60Hz
Iout = 350mA dim. 180x90x68**

Design iGuzzini

iGuzzini

Last information update: July 2024



Accessory code

X213: Constant current power supply unit DALI with outgoing cables IP68 25W - VIN =110-240VAC 50/60Hz Iout = 350mA dim. 180x90x68

Technical description

25W, 350 mA, IP68 constant current DALI power supply with a high-strength thermoplastic box and outlet cables. Stainless steel closure cable clamps. Vout=74Vdc (SELV), Iout=350 mA

Installation

The power supply box is not suitable for permanent immersion, for example in swimming pools or fountains.

Colour
Indeterminate (00)

Weight (Kg)
0.77

Dimension (mm) (*)
180x90x70

* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.

Wiring

The box is supplied with 2 separate 1500 mm long outlet cables. - A 4-conductor primary and check cable (L N DA DA) including an anti-transpiration device. - A 2-conductor secondary cable (+ -). The conductors have a cross section of 1 mm²

Notes

For IP connection accessories and the min/max number of products that can be connected, see the descriptions in the instruction sheet.

Complies with EN60598-1 and pertinent regulations



Technical data

Frequency [Hz]:	50/60	Minimum dimming %:	1
Current out [mA]:	350	Overvoltage protection:	4kV Common mode & 4kV Differential mode
Inrush current:	10 A / 200 µs	Control:	DALI-2
Maximum number of LED power supply units of this type per miniature circuit breaker:	B10A: 18 power supply units B16A: 30 power supply units C10A: 31 power supply units C16A: 51 power supply units		