

**Constant current power supply unit DALI with outgoing cables IP68 35W - VIN =110-240VAC 50/60Hz
Iout = 500mA dim. 180x90x68**

Design iGuzzini

iGuzzini

Last information update: July 2024



Accessory code

X216: Constant current power supply unit DALI with outgoing cables IP68 35W - VIN =110-240VAC 50/60Hz Iout = 500mA dim. 180x90x68

Technical description

35 W, 500 mA, IP68 constant current DALI power supply with a high-strength thermoplastic box and outlet cables. Stainless steel closure cable clamps. Vout=74Vdc (SELV), Iout=500 mA

Installation

The power supply box is not suitable for permanent immersion, for example in swimming pools or fountains.

Colour
Indeterminate (00)

Weight (Kg)
0.77

Dimension (mm) (*)
180x90x70

* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.

Wiring

The box is supplied with 2 separate 1500 mm long outlet cables. - A 4-conductor primary and check cable (L N DA DA) including an anti-transpiration device. - A 2-conductor secondary cable (+ -). The conductors have a cross section of 1 mm²

Notes

For IP connection accessories and the min/max number of products that can be connected, see the descriptions in the instruction sheet.

Complies with EN60598-1 and pertinent regulations



Technical data

Frequency [Hz]: 50/60

Current out [mA]: 500

Inrush current: 10 A / 200 µs

Maximum number of LED power supply units of this type per miniature circuit breaker:
B10A: 18 power supply units
B16A: 30 power supply units
C10A: 31 power supply units
C16A: 51 power supply units

Minimum dimming %: 1

Overvoltage protection: 4kV Common mode & 4kV Differential mode