

## For TCI drivers:

visit <https://www.tci.it/en/products/led-drivers/7984/milanoiled-75w-200-1050-1pn/> and download the software clicking on the link on the bottom-right.

[HOME](#)
[COMPANY](#)
[PRODUCTS](#)
[SALES CONTACTS](#)
[EVENTS](#)
[CATALOGUES & MEDIA](#)
[CONTACTS](#)

search engine powered by

### FEATURES

Rated Voltage 220...240 V

Constant Current

Dimming: MIDNIGHT Function  
FULL PROGRAMMABLE

Additional technical features: RIPPLE FREE  
ACTIVE PFC (pf>0.9)  
SELV >60V<>  
DIMMING: AMPLITUDE (AM)  
IEEE1789-2015 - Dim-to-Warm  
4/5 kV DM/CM SURGE Input Protection  
4/8 kV DM/CM SURGE Input Protection  
6/6 kV DM/CM SURGE Input Protection  
6/8 kV DM/CM SURGE Input Protection  
6/10 kV DM/CM SURGE Input Protection  
EXTERNAL NTC INPUT  
Suitable for AUTOMATIC WIRING MACHINE

Approvals: ENEC  
CCC  
RCM  
CE  
EAC

Plastic case: Square for Built-in

Size: 133 x 40 x 77 mm

last update: 7/15/2021

### Documentation download

MILANOILED 75W/200-1050 1PN (995 kb)

Photo (119 kb)

3D design (2 Mb)

### Approvals download

CE (257 kb)

ENEC (351 kb)

CB CERTIFICATE (315 kb)

ATTESTATION OF CONFORMITY EMC (370 kb)

RCM (1 Mb)

CCC (2 Mb)

EAC (1 Mb)

### Software

[download](#)